

TASK circle

suspended

EN Ring-shaped suspended luminaire, consisting of single elements in quarter circle or rectangular shape; Luminaire housing made of aluminium – rounded edges; ultra low-profile design (only 15 mm); surface powder coated; cable suspension, tool-less height adjustment; convenient quick mounting system without tools; incl. transparent feed; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-eff. LEDs – very good colour rendering; canopy for through wiring; optional acoustic elements available


FR Luminaire suspendu circulaire, composé d'éléments individuels en forme de quart-de-cercle ou de rectangle; Corps du luminaire en aluminium - bords arrondis; forme extrêm. plate (15 mm seulement); surface thermolaquée; suspension à câble réglable en hauteur sans outil; système de montage rapide, convivial et sans outil; incl. conduit d'alimentation transparent; distribution de lumière directe par LGP-Body (Light Guiding Prism); lumière couplée latéralement guidée vers le bas par gravure laser; partie indirecte avec platines dédiées pour un flux lumineux accru et un éclairage maximal du plafond; éclairage parfaitement homogène; LED à haut rend. énerg. – excellent rendu coul.; cache-piton pour câblage continu; en option : éléments acoustiques disponible

Quickinfo

4000 K
CRI ≥ 90, 3 SDCM
UGR ≤ 19 / 65° ≤ 3000 cd/m²
up to 117 lm/W
L95 @ 50 000 h
DALI-2
microprismatic (UGR ≤ 19)

acoustic elements
PET felt
♻️ from recycled material
up to absorption class A
🔥 available as B-s1, d0


Types



Luminaire colours



Acoustic colours




Light distribution




DiiA® standards
251, 252, 253




click-
system



DIN EN 12464-1
UGR ≤ 19



acoustic
elements



CRI ≥ 98
XPECTRUM

Order options

COLOUR TEMPERATURE

4000 K

CONTROL

DALI-2

LUMINAIRE COLOUR

○ pure white RAL 9010 7
● jet black RAL 9005 8

ACOUSTIC COLOUR

○ white W
● marble grey D
● felt grey G
● black L
● special colours p. 992 X

LIGHT OPTIC COVER

microprismatic (UGR ≤ 19)

Options on request




COLOUR RENDERING INDEX

CRI ≥ 80

CRI ≥ 98 XPECTRUM

FORM

for other configurations see
TASK S suspended system



TASK circle suspended



DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
169 W	4000 K	12900/± 6870 lm	0 5 9 - 5 2 8 1 1 3 K


TASK long circle suspended



DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
252 W	4000 K	20200/± 10460 lm	0 5 9 - 5 2 8 2 1 3 K

Technical data



TASK long circle
252 W, 4000 K, direct/indirect power

ROOM VALUES

Room dimensions	5,4 × 4 × 2,8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Suspension height	2.25 m


CALCULATION SURFACE

Surface dimensions	3.2 × 1.2 m
Surface height	0.75 m
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Light distribution




microprismatic
direct/indirect power

LUMINOUS FLUX value calculated for
CRI ≥ 90, colour white, cover microprismatic


Acoustic elements

TASK ACOUSTIC inlay

TYPE	L-W-H (mm)	ORDER CODE
1 TASK circle suspended	1155-1155-30	0 5 9 - 5 7 9 7 3 6
2 TASK long circle suspended	1155-2346-30	0 5 9 - 5 7 9 7 3 8



ø1500



2700