



## VELA

surface / ceiling


**EN** Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface powder coated; quick mounting system without tools; highly reflective coating of the PCB for improved efficiency; completely homogeneously illuminated, satinised PMMA cover; up to ø600 mm: microprismatic PMMA cover; either with direct or direct / indirect light distribution; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**FR** Corps de luminaire rond en aluminium, profil roulé, soudé sans trace visible ; surface thermolaquée ; système de montage rapide, sans outil ; revêtement hautement réfléchissant sur la platine pour une meilleure efficacité énergétique ; cache PMMA, à éclairage parfaitement homogène, satiné ; jusqu'à ø 600 mm : cache PMMA microprismatique ; au choix avec caractéristique de rayonnement direct ou direct / indirect ; LED économes en énergie à restitution de couleur élevée ; luminaire avec 2 ouvertures câblage et borne enfichable pour câblage passant

### Quickinfo

3000 K, 4000 K, tunable white  
2700 K - 6500 K  
CRI ≥ 80 / 3 SDCM  
UGR ≤ 19  
jusqu'à ↓ 6,360 lm / ↑ 194 lm  
jusqu'à 142 lm/W  
L80 / 50000 h, L90 / 50000 h  
DALI-2, non DIM  
Microprismatic, Opal  
IP40

### Types



### Couleur



### Répartition de la lumière



Diia® standards  
251, 252, 253




DIN EN 12464-1  
UGR ≤ 19




easy mounting  
by click-  
mechanism




tunable white  
2700 – 6500 K



CRI ≥ 98  
**XPECTRUM**  
(optional)



### VELA 300 surface



#### MICROPRISMATIC | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.1 W	3000 K	979 lm	97 lm/W	0 7 3 - 1 1 3 1 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
	4000 K	1040 lm	103 lm/W	0 7 3 - 1 1 3 1 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
17.3 W	tunable w.	1760 lm	102 lm/W	0 7 3 - 1 1 3 2 D 3 <input checked="" type="checkbox"/> K

#### OPAL | DIRECT CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.1 W	3000 K	993 lm	98 lm/W	0 7 3 - 1 1 3 1 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	1050 lm	104 lm/W	0 7 3 - 1 1 3 1 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
16.5 W	3000 K	1700 lm	103 lm/W	0 7 3 - 1 1 3 2 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	1800 lm	109 lm/W	0 7 3 - 1 1 3 2 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
17.3 W	tunable w.	1790 lm	103 lm/W	0 7 3 - 1 1 3 2 D 3 <input checked="" type="checkbox"/> O

#### MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.1 W	3000 K	↓1010/±58 lm	106 lm/W	0 7 3 - 1 1 3 7 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
	4000 K	↓1080/±62 lm	113 lm/W	0 7 3 - 1 1 3 7 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
17.3 W	tunable w.	↓1830/±104 lm	112 lm/W	0 7 3 - 1 1 3 8 D 3 <input checked="" type="checkbox"/> K

#### OPAL | DIRECT / INDIRECT SOFT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.1 W	3000 K	↓1050/±51 lm	109 lm/W	0 7 3 - 1 1 3 7 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓1110/±54 lm	115 lm/W	0 7 3 - 1 1 3 7 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
16.5 W	3000 K	↓1790/±87 lm	114 lm/W	0 7 3 - 1 1 3 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓1900/±92 lm	121 lm/W	0 7 3 - 1 1 3 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
17.3 W	tunable w.	↓1890/±92 lm	114 lm/W	0 7 3 - 1 1 3 8 D 3 <input checked="" type="checkbox"/> O



### VELA 450 surface



#### MICROPRISMATIC | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
16.7 W	3000 K	2060 lm	123 lm/W	0 7 3 - 1 1 4 1 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
	4000 K	2180 lm	131 lm/W	0 7 3 - 1 1 4 1 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
30.0 W	tunable w.	3560 lm	119 lm/W	0 7 3 - 1 1 4 2 D 3 <input checked="" type="checkbox"/> K

#### OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
16.7 W	3000 K	2050 lm	123 lm/W	0 7 3 - 1 1 4 1 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	2170 lm	130 lm/W	0 7 3 - 1 1 4 1 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
30.0 W	3000 K	3420 lm	114 lm/W	0 7 3 - 1 1 4 2 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	3620 lm	121 lm/W	0 7 3 - 1 1 4 2 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	tunable w.	3540 lm	118 lm/W	0 7 3 - 1 1 4 2 D 3 <input checked="" type="checkbox"/> O

#### Order options


<b>CONTROL</b>	<input checked="" type="checkbox"/>	<b>COLOUR</b>	<input checked="" type="checkbox"/>
non DIM	1	pure white RAL 9010	7
DALI-2	3	jet black RAL 9005	8
		white aluminium RAL 9006	G
		<a href="#">special colours</a>	X

**MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 80**


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
16.7 W	3000 K	↓2040/±83 lm	127 lm/W	0 7 3 - 1 1 4 7 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
	4000 K	↓2150/±87 lm	134 lm/W	0 7 3 - 1 1 4 7 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
30.0 W	tunable w.	↓3520/±142 lm	122 lm/W	0 7 3 - 1 1 4 8 D 3 <input checked="" type="checkbox"/> K

**OPAL | DIRECT / INDIRECT SOFT CRI ≥ 80**

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
16.7 W	3000 K	↓2020/±79 lm	126 lm/W	0 7 3 - 1 1 4 7 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓2150/±84 lm	134 lm/W	0 7 3 - 1 1 4 7 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
30.0 W	3000 K	↓3380/±132 lm	117 lm/W	0 7 3 - 1 1 4 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓3580/±140 lm	124 lm/W	0 7 3 - 1 1 4 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	tunable w.	↓3500/±137 lm	121 lm/W	0 7 3 - 1 1 4 8 D 3 <input checked="" type="checkbox"/> O

**VELA 600 surface****MICROPRISMATIC | DIRECT CRI ≥ 80**

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
31.0 W	3000 K	4060 lm	131 lm/W	0 7 3 - 1 1 5 1 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
	4000 K	4300 lm	139 lm/W	0 7 3 - 1 1 5 1 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
51.0 W	tunable w.	6400 lm	125 lm/W	0 7 3 - 1 1 5 2 D 3 <input checked="" type="checkbox"/> K

**OPAL | DIRECT CRI ≥ 80**

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
31.0 W	3000 K	4020 lm	130 lm/W	0 7 3 - 1 1 5 1 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	4250 lm	137 lm/W	0 7 3 - 1 1 5 1 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
48.0 W	3000 K	5930 lm	124 lm/W	0 7 3 - 1 1 5 2 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	6280 lm	131 lm/W	0 7 3 - 1 1 5 2 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
51.0 W	tunable w.	6340 lm	124 lm/W	0 7 3 - 1 1 5 2 D 3 <input checked="" type="checkbox"/> O

**MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 80**

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
31.0 W	3000 K	↓4030/±123 lm	134 lm/W	0 7 3 - 1 1 5 7 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
	4000 K	↓4260/±130 lm	142 lm/W	0 7 3 - 1 1 5 7 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> K
51.0 W	tunable w.	↓6360/±194 lm	128 lm/W	0 7 3 - 1 1 5 8 D 3 <input checked="" type="checkbox"/> K

**OPAL | DIRECT / INDIRECT SOFT CRI ≥ 80**

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
31.0 W	3000 K	↓3990/±111 lm	132 lm/W	0 7 3 - 1 1 5 7 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓4220/±118 lm	140 lm/W	0 7 3 - 1 1 5 7 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
48.0 W	3000 K	↓5900/±165 lm	126 lm/W	0 7 3 - 1 1 5 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓6240/±174 lm	134 lm/W	0 7 3 - 1 1 5 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
51.0 W	tunable w.	↓6290/±176 lm	127 lm/W	0 7 3 - 1 1 5 8 D 3 <input checked="" type="checkbox"/> O

**Order options**

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	jet black RAL 9005	8
		white aluminium RAL 9006	G
		special colours	X




### VELA 900 ceiling



#### MICROPRISMATIC | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	9020 lm	127 lm/W	0 7 3 - 1 1 7 1 5 3 <input checked="" type="checkbox"/> K
	4000 K	9560 lm	135 lm/W	0 7 3 - 1 1 7 1 6 3 <input checked="" type="checkbox"/> K



#### OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	8990 lm	127 lm/W	0 7 3 - 1 1 7 1 5 3 <input checked="" type="checkbox"/> O
	4000 K	9520 lm	134 lm/W	0 7 3 - 1 1 7 1 6 3 <input checked="" type="checkbox"/> O




### VELA 1200 ceiling



#### MICROPRISMATIC | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
147.0 W	3000 K	19400 lm	132 lm/W	0 7 3 - 1 1 8 1 5 3 <input checked="" type="checkbox"/> K
	4000 K	20500 lm	139 lm/W	0 7 3 - 1 1 8 1 6 3 <input checked="" type="checkbox"/> K



#### OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
147.0 W	3000 K	19400 lm	132 lm/W	0 7 3 - 1 1 8 1 5 3 <input checked="" type="checkbox"/> O
	4000 K	20600 lm	140 lm/W	0 7 3 - 1 1 8 1 6 3 <input checked="" type="checkbox"/> O

## Mounting accessories (optional)

### DISMOUNTING TOOL

TYPE	ORDER CODE
for ø600/900/1200	0 7 3 - 1 1 0 0 0 0 0

## Order options

COLOUR	
pure white RAL 9010	7 <input checked="" type="checkbox"/>
jet black RAL 9005	8
white aluminium RAL 9006	G
special colours	X

# Landeskrlinikum, Neunkirchen

Autriche

## Photographe

Kurt Kuball



## Produits utilisés



**VELA surface /  
ceiling**



**VELA suspended**

