



TUBO 60

suspended


EN Supporting profile in extruded aluminium; end cap in aluminium; surface powder coated; suspended luminaire with cable suspension; height adjustment without tools; incl. feeder cable; light control via high quality lens system for maximum, homogeneous illumination; completely homogeneously illuminated, cylindrical HPO (High Performance Opal) cover; energy-efficient LEDs with very good colour rendering

FR Profilé portant en profil extrudé en aluminium ; couvercle final en aluminium ; surface thermolaquée ; luminaire à suspension avec câble ; réglage en hauteur sans outil ; incl. conduit d'alimentation ; conduction de la lumière par optique à lentille pour un éclairage max. et homogène ; diffuseur HPO (High Performance Opal) cylindrique à éclairage entièrement homogène ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM
jusqu'à 3,060 lm/m
jusqu'à 133 lm/W
L90 / 50000 h
DALI-2
High Performance Opal
IP20

Types



Couleur




Répartition de la lumière




driver
integrated



system solution




uniform
illumination



TUBO 60 suspended



OPAL DALI-2



SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
13.9 W	625 mm	3000 K	80	1590 lm	114 lm/W	0 5 8 - 3 2 1 2 5 3 ☒ O
			90	1370 lm	99 lm/W	0 5 8 - 3 2 1 2 0 3 ☒ O
		4000 K	80	1810 lm	130 lm/W	0 5 8 - 3 2 1 2 6 3 ☒ O
			90	1480 lm	106 lm/W	0 5 8 - 3 2 1 2 1 3 ☒ O
27.9 W	1210 mm	3000 K	80	3180 lm	114 lm/W	0 5 8 - 3 2 1 4 5 3 ☒ O
			90	2740 lm	98 lm/W	0 5 8 - 3 2 1 4 0 3 ☒ O
		4000 K	80	3620 lm	130 lm/W	0 5 8 - 3 2 1 4 6 3 ☒ O
			90	2960 lm	106 lm/W	0 5 8 - 3 2 1 4 1 3 ☒ O
34.0 W	1500 mm	3000 K	80	3950 lm	116 lm/W	0 5 8 - 3 2 1 5 5 3 ☒ O
			90	3400 lm	100 lm/W	0 5 8 - 3 2 1 5 0 3 ☒ O
		4000 K	80	4490 lm	132 lm/W	0 5 8 - 3 2 1 5 6 3 ☒ O
			90	3670 lm	108 lm/W	0 5 8 - 3 2 1 5 1 3 ☒ O
54.0 W	2375 mm	3000 K	80	6300 lm	117 lm/W	0 5 8 - 3 2 1 8 5 3 ☒ O
			90	5430 lm	101 lm/W	0 5 8 - 3 2 1 8 0 3 ☒ O
		4000 K	80	7170 lm	133 lm/W	0 5 8 - 3 2 1 8 6 3 ☒ O
			90	5870 lm	109 lm/W	0 5 8 - 3 2 1 8 1 3 ☒ O

Order options

COLOUR	
pure white RAL 9010	☒ 7
jet black RAL 9005	☒ 8

Office, Amsterdam


Pays-Bas

Architecte
MVSA Architects

Photographe
Kris Dekeijser



Produits utilisés



TUBO 60 suspended

