



TUBO 60

surface / suspended


EN Supporting profile in extruded aluminium; end cap in aluminium; surface powder coated; suitable for wall or ceiling mounting (TUBO 60 surface); surface mounted or suspended luminaire with cable suspension; height adjustment without tools; with transparent feeder cable; light control via high-quality lens system for maximum, homogeneous illumination; completely homogeneously illuminated, cylindrical HPO (High Performance Opal) cover; energy-efficient LEDs with very good colour rendering

FR Profilé portant en profil extrudé en aluminium ; couvercle final en aluminium ; surface thermolaquée ; convient au montage mur ou plafond (TUBO 60 surface) ; luminaire en saillie ou suspendu avec câble de suspension ; réglage en hauteur sans outil ; conduit d'alimentation transparent inclus ; conduction de la lumière par optique à lentille pour un éclairage max. et homogène ; diffuseur HPO (High Performance Opal) cylindrique à éclairage entièrement homogène ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000K, 4000K
CRI ≥ 80, 3 SDCM
up to 114 lm/W
L90 @ 50 000h
DALI-2
opal


Types



Colours




Light distributions



driver
integrated



system
solution (p. 952)



uniform
illumination

Order options

COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL


DALI-2

MATERIAL COLOUR


○ pure white RAL 9010	7
● jet black RAL 9005	8

LIGHT OPTIC COVER

opal




TUBO 60 surface



LUMINAIRE

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
16.5 W	3000K	1780 lm	625	0 5 8 - 3 1 1 2 : 3 O
	4000K	1880 lm		
33 W	3000K	3560 lm	1210	0 5 8 - 3 1 1 4 : 3 O
	4000K	3760 lm		
37 W	3000K	4130 lm	1500	0 5 8 - 3 1 1 5 : 3 O
	4000K	4290 lm		
66 W	3000K	7110 lm	2375	0 5 8 - 3 1 1 8 : 3 O
	4000K	7530 lm		




TUBO 60 suspended



LUMINAIRE

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
16.5 W	3000K	1780 lm	625	0 5 8 - 3 2 1 2 : 3 O
	4000K	1880 lm		
33 W	3000K	3560 lm	1210	0 5 8 - 3 2 1 4 : 3 O
	4000K	3760 lm		
37 W	3000K	4130 lm	1500	0 5 8 - 3 2 1 5 : 3 O
	4000K	4290 lm		
66 W	3000K	7110 lm	2375	0 5 8 - 3 2 1 8 : 3 O
	4000K	7530 lm		

Light distribution



opal
direct

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, cover opal