



SQUADRO wallwasher

track


EN Track light in die cast aluminium in two different types (4 lamps or 2x4 lamps) and with 2 types of light modules (for shelf floor washer and wall floor washer); surface powder coated; aisle spotlight with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone, adjustable light modules; COB (Chip on Board) technology for maximum efficiency; efficient LEDs with very good colour rendering; IP 40 protection glass available as an accessory; including attachment for linear alignment of the spotlights

FR Spot sur rail en aluminium moulé en 2 variantes différentes (à 4 lampes ou 2 x 4 lampes) avec deux modules lumineux différents (pour shelf floor washer et wall floor washer) ; surface thermolaquée ; Spot pour couloirs avec réflecteurs spéciaux multiples dotés d'une technologie à forme libre avec optique à facettes pour un guidage extrêmement précis du flux lumineux ; éclairage précis des étagères et des couloirs, anti-éblouissement longitudinal optimal pour un confort visuel élevé dans les couloirs, modules lumineux réglables ; Technologie COB (Chip on Board) pour efficacité maximale ; LED économes en énergie à restitution de couleur élevée ; verre de protection IP 40 disponible comme accessoire ; y compris la fixation pour l'alignement linéaire des projecteurs

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
jusqu'à 134 lm/W
L80 / 50000 h
DALI-2, non DIM
IP20

Types



Couleur




Répartition de la lumière




compatible with
MOVE IT PRO



DiiA® standards
251, 252, 253



glare-free
reflector
longitudinally &
transversely



+20° up to -15°
tiltable




SQUADRO 1 x 4 lamps wallwasher track



SHELF FLOOR WASHER CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
51.0 W	3000 K	6010 lm	118 lm/W	1 4 9 - 2 2 3 1 5 ☒ ☒ S
	4000 K	6380 lm	125 lm/W	1 4 9 - 2 2 3 1 6 ☒ ☒ S



WALL FLOOR WASHER CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
51.0 W	3000 K	6100 lm	120 lm/W	1 4 9 - 2 2 3 1 5 ☒ ☒ A
	4000 K	6470 lm	127 lm/W	1 4 9 - 2 2 3 1 6 ☒ ☒ A




SQUADRO 2 x 4 lamps wallwasher track



SHELF FLOOR WASHER CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
86.0 W	3000 K	10600 lm	123 lm/W	1 4 9 - 2 2 4 0 5 ☒ ☒ S
	4000 K	11400 lm	133 lm/W	1 4 9 - 2 2 4 0 6 ☒ ☒ S
101.0 W	3000 K	12000 lm	119 lm/W	1 4 9 - 2 2 4 1 5 ☒ ☒ S
	4000 K	12800 lm	127 lm/W	1 4 9 - 2 2 4 1 6 ☒ ☒ S



WALL FLOOR WASHER CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
86.0 W	3000 K	10800 lm	126 lm/W	1 4 9 - 2 2 4 0 5 ☒ ☒ A
	4000 K	11500 lm	134 lm/W	1 4 9 - 2 2 4 0 6 ☒ ☒ A
101.0 W	3000 K	12200 lm	121 lm/W	1 4 9 - 2 2 4 1 5 ☒ ☒ A
	4000 K	12900 lm	128 lm/W	1 4 9 - 2 2 4 1 6 ☒ ☒ A

1 X SHELF / 1 X WALL FLOOR WASHER CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
86.0 W	3000 K	10700 lm	124 lm/W	1 4 9 - 2 2 4 0 5 ☒ ☒ B
	4000 K	11500 lm	134 lm/W	1 4 9 - 2 2 4 0 6 ☒ ☒ B
101.0 W	3000 K	12100 lm	120 lm/W	1 4 9 - 2 2 4 1 5 ☒ ☒ B
	4000 K	12800 lm	127 lm/W	1 4 9 - 2 2 4 1 6 ☒ ☒ B

Order options


CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8

Planning Information

SQUADRO shelf floor washer, 1×4 lamps, +5° tilt, 51W, 3000K



SQUADRO wall floor washer, 1×4 lamps, +5° tilt, 51W, 3000K



ROOM VALUES		CALCULATION SURFACE	
Wall dimensions	H = 3.5 m W = 10.8 m	Surface dimensions	10.8 × 3.5 m
Distance to wall	B = 1.3 m	Surface height	0 – 3.5 m
Aisle width	2.6 m		
Reflection factor	0.7 0.7 0.2	Eye level 	1.35 m – 1.75 m
Maintenance factor	0.9		

Optical accessories (optional)

IP40 PROTECTION GLASS

TYPE	ORDER CODE
1 x 4 lamps / single-sided	0 4 9 - 2 9 3 0 0 1 0
2 x 4 lamps / double-sided	0 4 9 - 2 9 4 0 0 1 0

Kerakoll Design House, Budapest

Hongrie

Architecte

Bence Tóth | Solinfo
Group

Lighting Design

Dávid Bodrogi

Photographe


Gosztom Gergő



Produits utilisés



SQUADRO
wallwasher track



BO 32 / 45 / 55
intrack



UNICO wall recessed



PIVOT MOVE IT 25 / 45



MITA circle 450
suspended



BO 32 / 45 / 55
intrack 1 | 2 | 3 lamps



MOVE IT PRO
surface / suspended
system



