



PABLO colour tune / tunable white

EN Track light made of die-cast aluminium; surface powder coated; 360° rotatable and 310° tiltable; converter in spotlight housing; COB (Chip on Board) technology or CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high quality aluminium reflector with spherical facet finish; high-gloss anodised; precise radiation characteristic with different light distributions; installed and exchanged without tools; optical attachments as accessories; adapter for tool-less insertion or movement on a variety of 3-phase power tracks; adapter fixation optionally without tools by means of knurled screw or set screw (screwdriver required); point outlet, either in surface mounted housing or recessed housing, available as an accessory

FR Spot sur rail en fonte d'aluminium injectée ; surface thermolaquée ; rotatif à 360° et orientable à 310° ; convertisseur dans boîtier de spot ; technologie COB (Chip on Board) ou CSP (Chip-Scale-Packaging) pour un rendement maximum ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de haute qualité en aluminium avec optique sphérique à facettes ; anodisé brillant ; caractéristique de diffusion précise avec différentes possibilités de répartitions de la lumière ; peut être installé ou changé sans outil ; éléments optiques comme accessoires ; adaptateur pour installation ou déplacement sans outil dans différents rails triphasés ; fixation de l'adaptateur au choix sans outils par vis moletée ou vis de serrage (tournevis nécessaire) ; point de sortie, au choix dans un boîtier en saillie ou comme variante pour encastrément, disponible comme accessoire

Quickinfo

3500 K, tunable white 2700 K - 5000 K
 CRI ≥ 90, CRI ≥ 98 / 3 SDCM
 jusqu'à 54 lm/W
 L85 / 50000 h, L95 / 50000 h
 DALI-2
 IP20

Types



Couleur



Répartition de la lumière



compatible with
MOVE IT PRO



DiiA® standards
251, 252, 253



360° rotatable,
310° tiltable



rotation lock



colour tune
(3500 K red /
blue)



tunable white
2700 – 5000 K



PABLO tunable white track




MEDIUM DALI-2, CRI ≥ 98

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
26.6 W	tunable w.	1140 lm	43 lm/W	1 8 0 - 5 6 0 D 3 M

FLOOD DALI-2, CRI ≥ 98

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
26.6 W	tunable w.	1080 lm	41 lm/W	1 8 0 - 5 6 0 D 3 F



PABLO colour tune track



MEDIUM DALI-2, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
18.8 W	3500 K	1020 lm	54 lm/W	1 8 0 - 5 6 0 G 3 M

FLOOD DALI-2, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
18.8 W	3500 K	939 lm	50 lm/W	1 8 0 - 5 6 0 G 3 F


Planning Information

Fresh colour for historical works of art



PABLO colour tune was developed to revitalise historical art, which is particularly worthy of protection, true to the original. An increased, individually adjustable red-blue saturation compensates for time-related colour damage – purely through the lighting. This reawakens the original colours of a work of art. The correct setting of PABLO colour tune can be easily controlled and adjusted via DALI-2.

Mounting accessories (optional)



RECESSED HOUSING / POINT OUTLET ceiling thickness, 1-30 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	151-60	1 8 6 - 0 7 2 2 7 7
jet black	151-60	1 8 6 - 0 7 2 2 7 8



SURFACE HOUSING / POINT OUTLET

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	120-32	1 8 6 - 0 7 2 2 8 7
jet black	120-32	1 8 6 - 0 7 2 2 8 8

Order options

MOUNTING	Ø	COLOUR	■
set screw (tool required)	1	traffic white RAL 9016	7
tool-free fixation	2	jet black RAL 9005	8

Optical accessories (optional)



ø 61

HONEYCOMB LOUVER

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 70 PABLO	jet black	61-3	0 8 0 - 5 9 0 0 0 1 8



ø 66

SNOOT

COLOUR	Ø-H (mm)	ORDER CODE
jet black	62-33	0 8 0 - 5 9 0 0 0 0 8