



SONO LOOP IP54

surface


EN Round luminaire housing in die-cast aluminium; surface powder coated; fitted bezel in rolled, seamless welded aluminium profile; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

FR Corps de luminaire rond en fonte d'aluminium injectée ; surface thermolaquée ; bague posée en profil d'aluminium roulé et soudé sans trace visible ; convient au montage mur ou plafond ; cache PMMA, à éclairage parfaitement homogène, satiné ; luminance identique pour toutes les variantes de taille ; LED économes en énergie à restitution de couleur élevée ; luminaire avec 2 ouvertures câblage et borne enfichable pour câblage passant

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, 3 SDCM
 up to 133lm/W
 L90 @ 50 000h
 non DIM, DALI-2
 opal cover
 IK 07, IP54

Types



Colours



Light distribution



direct




DiiA® standards
 251, 252, 253



easy mounting by
 click-mechanism



dust and insect
 protection (IP54)



tunable white
 2700–6500K

Order options

IP RATING

IP54

COLOUR TEMPERATURE

3000K 5
4000K 6

CONTROL

non DIM 1
DALI-2 3

MATERIAL COLOUR

○ pure white RAL 9010 7
● grey aluminium RAL 9007 D

LIGHT OPTIC COVER

opal

Options on request

COLOUR RENDERING INDEX


CRI ≥ 90

COLOUR TEMPERATURE


tunable white 2700–6500K
DALI-2 DT8

CONTROL

RCS Master (☺)
RCS Slave (☺)




SONO LOOP 260 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
7.6W	3000K	881lm	8 7 1 - 8 1 2 6 :: ◆ ◆ ○
	4000K	933lm	




SONO LOOP 350 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15.9W	3000K	1940lm	8 7 1 - 8 1 3 6 :: ◆ ◆ ○
	4000K	2060lm	




SONO LOOP 450 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.2W	3000K	2850lm	8 7 1 - 8 1 4 6 :: ◆ ◆ ○
	4000K	3010lm	



SONO LOOP 600 surface



IP54 LUMINAIRE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
43W	3000K	5410lm	8 7 1 - 8 1 5 6 :: ◆ ◆ ○
	4000K	5730lm	