

# BETO direct / indirect power

free standing T-shape  
074-695561XR



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Sol, Sur pied \_\_\_\_\_

couleurs spéciales \_\_\_\_\_

Réflecteur chrome \_\_\_\_\_

IP20 \_\_\_\_\_

Indirect 7550 lm \_\_\_\_\_

direct 2300 lm \_\_\_\_\_

total 9850 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI  $\geq 80$  \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam initial  $\leq 3$  SDCM \_\_\_\_\_

MR 0.72 \_\_\_\_\_

MDER 0.65 \_\_\_\_\_

## Optique

Reflector \_\_\_\_\_

Asymmetric \_\_\_\_\_

UGR  $< 13$  \_\_\_\_\_

PstLM  $\leq 1.0$  <sup>1</sup> \_\_\_\_\_

SVM  $\leq 0.4$  <sup>1</sup> \_\_\_\_\_

## Electrique

DIM tactile sur tige \_\_\_\_\_

66 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

149 lm/W \_\_\_\_\_

## Physique

T-shape \_\_\_\_\_


longueur 1055 mm \_\_\_\_\_

largeur 42 mm \_\_\_\_\_


hauteur 2100 mm \_\_\_\_\_

<sup>1</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage

