

# VELA 600 direct / indirect power

suspended  
073-1254638K



Projet / Type  
Notes  
Quantité / Date



## Général

Plafond , Suspendu  
noir , RAL9005 <sup>1</sup>  
IP40  
Indirect 1970 lm  
direct 4390 lm  
total 6360 lm

## LED

4000 K  
CRI  $\geq 80$   
L90 / 50000 h  
sécurité photobio. RG 0 - aucun risque  
MacAdam initial  $\leq 3$  SDCM  
MR 0.72  
MDER 0.66

## Optique

Microprismatic  
UGR  $< 19$  ,  $\geq 65^\circ$   $< 3000$  cd/m<sup>2</sup>  
PstLM  $\leq 1.0$  <sup>2</sup>  
SVM  $\leq 0.4$  <sup>2</sup>

## Electrique


DALI-2  
45 W  
CP1 220-240V  
141 lm/W  
1 DALI Addr.

## Physique


câble 1500 mm  
diamètre 600 mm  
hauteur 87 mm  
5.8 kg

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

