

# MOVE IN 45 flex round

trim

063-8221418F 063-8822118 002-90724



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



**Général**

Plafond , Demi-encastré

inclinaison max 90°

rotation 360°

noir , RAL9005 <sup>1</sup>

Set de montage Noir profond

IP20

1230 lm

**LED**

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.53

MDER 0.48

**Optique**

flood

angle de faisceau 36°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

**Electrique**

non DIM

15.9 W

CP2 220-240V

77 lm/W

**Physique**

bord

diamètre 77 mm

hauteur 107 mm

0.33 kg

**Découpe**

diamètre 65 mm

épaisseur min. du plafond 2 mm

épaisseur max. du plafond 25 mm

profondeur de l'encastrement 200 mm

<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)



## Répartition de la lumière



flood 36°

h (m)	E0° (lx)	ø (m)
1	3660	0.65
2	920	1.29
3	410	1.94
4	230	2.59
5	150	3.23

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

