

# MOVE IT 25 S track

## indirect


050-741951G



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



### Général

Plafond , Suspendu \_\_\_\_\_

or , gold dust/RAL9005 <sup>1</sup> \_\_\_\_\_

Couleur intérieure noir \_\_\_\_\_

1670 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

6000 lm \_\_\_\_\_

### LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

### Electrique

non DIM \_\_\_\_\_

51 W \_\_\_\_\_

CP3 48V \_\_\_\_\_

118 lm/W \_\_\_\_\_

14 W/m \_\_\_\_\_

### Physique

longueur 3625 mm \_\_\_\_\_


largeur 31 mm \_\_\_\_\_

hauteur 31 mm \_\_\_\_\_


2 kg \_\_\_\_\_

<sup>1</sup> Code RAL

### Répartition de la lumière



### Dessin de fabrication



### Notice de montage



### Calculateur d'éclairage

