

# MOVE IT 25 S track corner

indirect

050-741101G



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Suspendu \_\_\_\_\_

or \_\_\_\_\_

Couleur intérieure noir \_\_\_\_\_

IP20 \_\_\_\_\_

1550 lm \_\_\_\_\_

15200 lm/m \_\_\_\_\_

insert optique 139 lm/W<sup>1</sup> \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

## Optique

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

48 V \_\_\_\_\_

luminaire 13.1 W \_\_\_\_\_

insert optique 11.2 W \_\_\_\_\_

CP3 \_\_\_\_\_

129 W/m \_\_\_\_\_

## Physique

longueur 637 mm \_\_\_\_\_


largeur 610 mm \_\_\_\_\_

hauteur 31 mm \_\_\_\_\_


1 kg \_\_\_\_\_

<sup>1</sup> y compris la prise en compte des pertes optiques.  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

