



LENO system

recessed trimless


EN Low profile recessed channel; for trimless installation in 12.5 mm plasterboard ceilings; wall or ceiling mounting; for lighting systems; powder coated; special edge design with grooves for better adhesion of filler; easy mounting without need to cut the substructure; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; optional asym. light distribution; energy-eff. LEDs – very good colour rendering; external converter for ceiling insertion

FR Canal à encastrer extrêmement plat ; montage sans bord dans plaf. en placopl. de 12,5mm ; montage mur ou plafond ; pour les systèmes d'éclairage ; thermolaquée ; formation de bords spéciaux avec cannelures pour meilleure adhérence du l'enduit ; montage simple sans découpage de la sous-construction ; élément d'éclairage antichute en profil d'aluminium extrudé pour montage en canal sans outil au moyen de fixations magnétiques ; lumière couplée latéralement guidée vers le bas par LGP Body (Light Guiding Prism) et réflecteur haut. efficace ; cache éclairé de façon homogène, satiné (affleurant ou en saillie) ou microprismatique en PMMA ; en option diffusion asym. de la lumière ; LED à haut rend. énerg. – excellent rendu coul. ; convertisseur externe pour fente plafond

Quickinfo

3000K, 4000K
 CRI ≥ 80, 3 SDCM
 up to 137lm/W
 L90 @ 50 000h
 DALI-2
 opal, microprismatic (UGR ≤ 19),
 jut-out, asymmetric wallwasher


Types



Colour




Light distributions



DiiA® standards
 251, 252, 253



single luminaire
 (p. 492)



microprismatic
 UGR ≤ 19



quick
 installation

Order options

COLOUR TEMPERATURE	☼☼
3000K	5
4000K	6

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016

LIGHT OPTIC COVER

opal high performance	H
microprismatic (UGR ≤ 19)	G
jut-out	J
asymmetric	A

Options on request


COLOUR RENDERING INDEX

CRI ≥ 90

EMERGENCY LIGHT


1h accupack
3h accupack

Light distribution



asymmetric

LUMINOUS FLUX value calculated for
colour white, cover opal
microprismatic -5%, jut-out-4%



LENO trimless

INSTALLATION CHANNEL

TYPE	L (mm)	ORDER CODE
channel	613	051-8900067
channel	1221	051-8900127
channel	1830	051-8900187
channel	2438	051-8900247

order installation channel, light inset + mounting accessories separately



LIGHT INSET

SYS. POWER (OPAL, MP, JUT-OUT / ASYM.)	L (mm)	ORDER CODE
10.8W / 15.6W	612	051-8012::37□
19.1W / 31W	1220	051-8014::37□
28.6W / 47W	1828	051-8016::37□
38W / 62W	2436	051-8018::37□

COVER	COLOUR TEMP.	SYSTEM POWER	DELIVERED LUMENS	EFFICACY
opal high	3000K	17.6W/m	2010lm/m	129lm/W
performance	4000K		2130lm/m	137lm/W
microprismatic	3000K	17.6W/m	1900lm/m	122lm/W
UGR ≤ 19	4000K		2010lm/m	129lm/W
jut-out	3000K	17.6W/m	1930lm/m	124lm/W
	4000K		2040lm/m	131lm/W
asymmetric	3000K	25.5W/m	2580lm/m	101lm/W
	4000K		2730lm/m	107lm/W

Accessories



END CAPS

TYPE	ORDER CODE
end caps (pair)	051-8990217



LINEAR CONNECTOR


TYPE	ORDER CODE
linear connector (pair)	051-8990110
linear connector (10 pairs)	051-8990110.10



DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	086-30000

Technical data



LENO trimless, microprismatic,
19.1W, 4000K

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

