

# OPAL HIGH PERFORMANCE

MOVE IT 25 S  
050-1212518H



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond / mur , Rail \_\_\_\_\_

noir , RAL 9005 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

864 lm \_\_\_\_\_

insert optique 116 lm/W<sup>2</sup> \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89 \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

## Optique

High Performance Opal \_\_\_\_\_

opal (lambertsch) \_\_\_\_\_

PstLM ≤ 1.0 <sup>3</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>3</sup> \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

48 V \_\_\_\_\_

luminaire 10.6 W \_\_\_\_\_

insert optique 7.4 W \_\_\_\_\_

CP3 \_\_\_\_\_

## Physique

longueur 605 mm \_\_\_\_\_


largeur 25 mm \_\_\_\_\_

hauteur 20 mm \_\_\_\_\_


0.3 kg \_\_\_\_\_

<sup>1</sup> Code RAL <sup>2</sup> y compris la prise en compte des pertes optiques.  
<sup>3</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage

