

JUST 45 MOVE IT 25 / 25 S / 45

050-0131D38M



Projet / Type

Notes

Quantité / Date



Général

Plafond / mur | Rail

inclinaison max 90°

rotation 360°

noir | RAL 9005 ¹

IP20

605 lm

insert optique 71 lm/W ²

LED

tunable white | 2700 K - 6500 K

CRI ≥ 90

L90 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 97 | R_r: 88 | R_{t(1-5)}: 88

MR 1.15 | MDER 1.04

Optique

medium | angle de faisceau 21°

PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrique

DALI-2 DT8 | 1 DALI Addr.

CP3 | 48 V

luminaire 11.3 W

insert optique 8.5 W

Physique


diamètre 45 mm | hauteur 68 mm

0.2 kg

¹ Code RAL ² y compris la prise en compte des pertes optiques.

³ Valeur du produit contenant à pleine charge (non atténué)


Répartition de la lumière



medium 21°

h (m)	EO° (lx)	ø (m)
1	3100	0.38
2	770	0.76
3	340	1.14
4	190	1.52
5	120	1.90

Dessin de fabrication



Notice de montage

