

# JUST 45

MOVE IT

050-0131518F



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Rail \_\_\_\_\_

inclinaison max 90° \_\_\_\_\_

rotation 360° \_\_\_\_\_

noir , RAL9005 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

799 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 98 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.62 \_\_\_\_\_

MDER 0.56 \_\_\_\_\_

## Optique

flood \_\_\_\_\_

angle de faisceau 44° \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

11.2 W \_\_\_\_\_

CP3 48V \_\_\_\_\_

71 lm/W \_\_\_\_\_


## Physique

diamètre 45 mm \_\_\_\_\_

hauteur 68 mm \_\_\_\_\_

0.2 kg \_\_\_\_\_

## Répartition de la lumière



flood 44°

h (m)	EO° (lx)	ø (m)
1	1480	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Dessin de fabrication



<sup>1</sup> Code RAL

## Notice de montage



## Calculateur d'éclairage

