

# ARY adjustable rod suspended canopy surface

049-5231617F 005-2602137



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



220-240V

220-240V

220-240V

220-240V

**Général**

Plafond , Suspendu

inclinaison max 90°

rotation 265°

blanc , RAL9016 <sup>1</sup>

cache-piton blanc signalisation

IP20

791 lm

**LED**

4000 K

CRI ≥ 90

L90 / 50000 h

MacAdam initial ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 89 , R<sub>t(1-5)</sub>: 87

MR 0.81

MDER 0.73

**Optique**

flood

angle de faisceau 44°

**Electrique**

DALI-2

11.2 W

CP2 220-240V

71 lm/W

1 DALI Addr.

**Physique**


barre de 1500 mm avec crochet

diamètre 47 mm

hauteur 110 mm


0.5 kg

## Répartition de la lumière



h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Dessin de fabrication



<sup>1</sup> Code RAL

## Notice de montage



## Calculateur d'éclairage

