

# ARY adjustable rod suspended canopy surface

049-5131417M 005-2601117



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Suspendu \_\_\_\_\_

inclinaison max 90° \_\_\_\_\_

rotation 265° \_\_\_\_\_

blanc , RAL 9016 <sup>1</sup> \_\_\_\_\_

cache-piton blanc signalisation \_\_\_\_\_

IP20 \_\_\_\_\_

642 lm \_\_\_\_\_

luminaire 76 lm/W<sup>2</sup> \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

## Optique

medium \_\_\_\_\_

angle de faisceau 25° \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

220-240 V \_\_\_\_\_

système 11.2 W \_\_\_\_\_

luminaire 8.4 W \_\_\_\_\_

18 Vf \_\_\_\_\_

500 mA \_\_\_\_\_

CP2 \_\_\_\_\_

## Physique

barre 1500 mm \_\_\_\_\_


diamètre 47 mm \_\_\_\_\_

hauteur 110 mm \_\_\_\_\_

0.62 kg \_\_\_\_\_

<sup>1</sup> Code RAL  
<sup>2</sup> y compris la prise en compte des pertes optiques et des pertes de l'unité de contrôle interne

## Répartition de la lumière



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

