

# SASSO 100 round adjustable

ceiling

048-34104379W



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



220-240V

360°

X-PERT

X-PERT

## Général

Plafond , Surface

inclinaison max 20°

rotation 360°

blanc , RAL9016/gold <sup>1</sup>

Réflecteur or

IP20

1560 lm

## LED

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.53

MDER 0.48

## Optique

wide flood

angle de faisceau 60°

UGR < 19 , ≥65° <1500 cd/m²

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrique

DALI-2

20.2 W

CP1 220-240V

77 lm/W

1 DALI Addr.


## Physique

diamètre 100 mm


hauteur 162 mm

0.95 kg

## Répartition de la lumière



## Dessin de fabrication



<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

