

# SASSO 100 round adjustable

ceiling

048-34104174W



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Surface \_\_\_\_\_

inclinaison max 20° \_\_\_\_\_

rotation 360° \_\_\_\_\_

blanc , RAL9016/matt silver <sup>1</sup> \_\_\_\_\_

Réflecteur argent mat \_\_\_\_\_

IP20 \_\_\_\_\_

1630 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optique

wide flood \_\_\_\_\_

angle de faisceau 60° \_\_\_\_\_

UGR < 19 , ≥65° <1500 cd/m<sup>2</sup> \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

20.2 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

81 lm/W \_\_\_\_\_

## Physique

diamètre 100 mm \_\_\_\_\_


hauteur 162 mm \_\_\_\_\_

0.95 kg \_\_\_\_\_


<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

