

# SASSO 60 base round adjustable 2 lamps

ceiling

048-31405377M



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



220-240V

360°

X-PERT

X-PERT

## Général

Plafond , Surface \_\_\_\_\_

inclinaison max 30° \_\_\_\_\_

rotation 360° \_\_\_\_\_

blanc , RAL9016/white <sup>1</sup> \_\_\_\_\_

Couleur intérieure blanc \_\_\_\_\_

IP20 \_\_\_\_\_

1740 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.53 \_\_\_\_\_

## Optique

medium \_\_\_\_\_

angle de faisceau 22° \_\_\_\_\_

UGR < 19 \_\_\_\_\_

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

21.7 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

80 lm/W \_\_\_\_\_

## Physique


longueur 260 mm \_\_\_\_\_

largeur 80 mm \_\_\_\_\_


hauteur 81 mm \_\_\_\_\_

0.75 kg \_\_\_\_\_

## Répartition de la lumière



## Dessin de fabrication



<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

