

SASSO 60 square downlight

trim

048-2612E19M 048-2697318 002-90762



Projet / Type

Notes

Quantité / Date



Général

Plafond , Encastré

or , RAL260-M¹

Set de montage Noir profond

avant IP40 , arrière IP20

752 lm

LED

colour warm dimming

1800 K - 3000 K

CRI ≥ 90

L85 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 101 , R_f: 94 , R_{t(1-5)}: 96

MR 0.64

MDER 0.58

Optique

medium

angle de faisceau 26°

UGR < 19

P_{stLM} ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

12.0 W

CP2 220-240V

63 lm/W

1 DALI Addr.

Physique

bord

longueur 80 mm

largeur 80 mm

hauteur 48 mm

0.28 kg

Découpe

longueur 73 mm

largeur 73 mm

épaisseur min. du plafond 2 mm

épaisseur max. du plafond 25 mm

profondeur de l'encastrement 100 mm

¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)


Notice de montage



Calculateur d'éclairage



Répartition de la lumière



Dessin de fabrication

