

SASSO 60 round downlight

trim 2 lamps

048-2602E19M 048-269831G 002-90762



Projet / Type

Notes

Quantité / Date



Général

Plafond , Encastré

rotation 360°

or , RAL260-M ¹

Set de montage gris argent

avant IP40 , arrière IP20

1470 lm

LED

colour warm dimming

1800 K - 3000 K

CRI ≥ 90

L85 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 101, R_r: 94, R_{1-15}: 96

MR 0.64

MDER 0.58

Optique

medium

angle de faisceau 26°

UGR < 19

P_{stLM} ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

24.0 W

nombre total d'inserts 20.4 W

CP2 220-240V

61 lm/W

1 DALI Addr.

Physique

bord

longueur 147 mm

largeur 80 mm

hauteur 48 mm

0.34 kg

Découpe

diamètre 70 mm

longueur 136 mm

épaisseur min. du plafond 2 mm


épaisseur max. du plafond 25 mm

profondeur de l'encastrement 110 mm

¹ Code RAL



² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication

90
non DIM
110
DALI-2
70 x 136



Notice de montage



Calculateur d'éclairage

