

# SASSO 60 round downlight

trimless

048-2602519M 048-2696117 002-90762



Projet / Type

Notes

Quantité / Date



## Général

Plafond , Encastré

rotation 360°

or , RAL260-M <sup>1</sup>

Set de montage blanc signalisation

avant IP44 , arrière IP20

931 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88

MR 0.59

MDER 0.53

## Optique

medium

angle de faisceau 21°

UGR < 16 , ≥ 65° < 3000 cd/m<sup>2</sup>

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrique

DALI-2

12.6 W

CP2 220-240V

74 lm/W

1 DALI Addr.

## Physique

sans bord

diamètre 73 mm

hauteur 48 mm

0.28 kg

## Découpe


diamètre 73 mm

profondeur de l'encastrement 120 mm

<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication

