

# SASSO 60 round downlight

trimless exposed concrete

048-2602417S 048-2695210 002-90771



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



↑ IP20  
↓ IP44

220-240V

360°

X-PERT

X-PERT

## Général

Plafond , Encastré

rotation 360°

blanc , RAL9016 <sup>1</sup>

avant IP44 , arrière IP20

539 lm

## LED

2700 K

CRI ≥ 90

MacAdam initial ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.53

MDER 0.48

## Optique

spot

angle de faisceau 11°

UGR < 19

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrique

non DIM

13.1 W

CP2 220-240V

41 lm/W

## Physique

sans bord

longueur 230 mm

largeur 230 mm

hauteur 162 mm


2.35 kg

## Découpe



profondeur de l'encastrement 90 mm

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

