

MINO CIRCLE

ceiling


EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; surface powder coated; light inset consisting of highly reflective coated die-cast aluminium for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; sound absorbing elements available; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en forme d'anneau en profil extrudé roulé en aluminium soudé sans trace visible ; surface thermolaquée ; élément lumineux composé d'aluminium moulé laqué hautement réfléchissant pour une gestion thermique améliorée ; cache HPO (High Performance Opal) pour éclairage homogène ; cache PMMA microprismatique, avec film diffusant inclus pour réduire la brillance avec un éclairage homogène ; éléments d'absorption acoustique disponible ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000K, 4000K
 CRI ≥ 80, 3 SDCM
 up to 123lm/W
 L90 @ 50 000h
 DALI-2
 opal, microprismatic

Types




Luminaire colours



Light distribution



DiiA® standards
 251, 252, 253



Order options

COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL	
DALI-2	


MATERIAL COLOUR	
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours	X

LIGHT OPTIC COVER	
opal high performance	H
microprismatic	Z


Options on request

COLOUR RENDERING INDEX	
CRI ≥ 90	

CONTROL	
Casambi	




MINO 60 CIRCLE 1000 ceiling




DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
65W	3000K	7130lm	034-2112::3□□
	4000K	7550lm	




MINO 60 CIRCLE 1500 ceiling




DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
99W	3000K	11400lm	034-2110::3□□
	4000K	12100lm	




MINO 60 CIRCLE 3000 ceiling




DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
198W	3000K	23000lm	034-2114::37H
	4000K	24300lm	

other configurations see MINO 60 CURVE system



MINO 60 CIRCLE 6000 ceiling



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
396W	3000K	45900lm	034-2116::37H
	4000K	48600lm	

other configurations see MINO 60 CURVE system

Acoustic elements

see page 608