




## Quickinfo

2700 K, 3000 K  
 CRI  $\geq$  90 / 2 SDCM, 3 SDCM  
 jusqu'à 95 lm/W  
 L90 / 50000 h  
 Casambi, DALI-2, non DIM  
 IP20

## Types



## Couleur



## cache-piton




## Répartition de la lumière




# TULA suspended

**EN** Decorative suspended luminaire in aluminium; surface polished chrome or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; good glare reduction due to recessed light point plane; incl. high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy, either recessed or surface mounted version; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory


**FR** Luminaire décoratif à suspension en aluminium ; surface chrome poli ou surface thermolaquée ; suspension par câble, câble d'alimentation inclus (noir ou blanche) ; recoupable à volonté ; bon anti-éblouissement grâce aux points lumineux en retrait ; incl. optique lentille de grande qualité ; avec technologie COB (Chip on Board) pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; cache-piton pour câblage continu ; convertisseur inclus dans le cache-piton, au choix en variante encastrée ou en saillie ; anneaux de montage au plafond pour un positionnement multiple des luminaires dans la pièce disponibles comme accessoires



free positioning  
by ring and  
hook



track version  
available



## TULA nano suspended




### MEDIUM CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.9 W, 500 mA	2700 K	790 lm	89 lm/W	0 4 9 - 5 H 1 0 4 1 M
	3000 K	816 lm	92 lm/W	0 4 9 - 5 H 1 0 5 1 M

### FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.9 W, 500 mA	2700 K	762 lm	86 lm/W	0 4 9 - 5 H 1 0 4 1 F
	3000 K	787 lm	89 lm/W	0 4 9 - 5 H 1 0 5 1 F



## TULA micro suspended




### MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.4 W, 500 mA	2700 K	648 lm	77 lm/W	0 4 9 - 5 H 1 5 4 1 M
	3000 K	746 lm	88 lm/W	0 4 9 - 5 H 1 5 5 1 M

### FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.4 W, 500 mA	2700 K	694 lm	82 lm/W	0 4 9 - 5 H 1 5 4 1 F
	3000 K	798 lm	95 lm/W	0 4 9 - 5 H 1 5 5 1 F

## Electrical mounting accessories (required)



### CANOPY for cable suspension 500 mA, PC2, 198-264 V AC

TYPE	COLOUR	EFFICIENCY	Ø-H (mm)	ORDER CODE
13 W   non DIM	traffic white	η 84 %	115:29	0 0 5 - 2 6 0 2 1 1 7
13 W   non DIM	jet black	η 84 %	115:29	0 0 5 - 2 6 0 2 1 1 8
10 W   DALI-2	jet black	η 85 %	115:29	0 0 5 - 2 6 0 2 1 3 8
10 W   Casambi	jet black	η 83 %	115:29	0 0 5 - 2 6 0 2 1 9 8

incl. power supply

### CANOPY for cable suspension 500 mA, 10 W, PC2, 198-264 V AC, traffic white

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
DALI-2	η 85 %	115:29	0 0 5 - 2 6 0 2 1 3 7
Casambi	η 83 %	115:29	0 0 5 - 2 6 0 2 1 9 7

incl. power supply

## Mounting accessories (required)




### MOUNTING SET trimless

TYPE	COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
for installation in plasterboard ceilings	traffic white	9-25 mm	75:48	0 0 5 - 3 5 1 1 0 1 7

excl. power supply

## Order options

HEIGHT	H	COLOUR	
300 mm	5	chrome	4
500 mm	7	traffic white RAL 9016	7
		jet black RAL 9005	8
		special colours	X

**MOUNTING SET with trim** for installation in ceilings, 2-25 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	77-49	0 0 5 - 3 5 2 1 0 1 7
jet black	77-49	0 0 5 - 3 5 2 1 0 1 8

excl. power supply

**Mounting accessories (optional)****HOOK ceiling mounted**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	18-58	0 5 0 - 0 5 1 0 3 1 7
jet black	18-58	0 5 0 - 0 5 1 0 3 1 8

**RING ceiling mounted**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	50-88	0 5 0 - 0 5 1 0 2 1 7
jet black	50-88	0 5 0 - 0 5 1 0 2 1 8

**SPECIAL MOUNTING TOOL**

TYPE	Ø-H (mm)	ORDER CODE
for ARY   MOVE IN 45   NOBA   TULA	100-107	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless


**Electrical accessories (required)****POWER SUPPLY** 500 mA, 10 W, PC2, 198-264 V AC

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 3 2
DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 3 3

**Electrical accessories (optional)****DIN RAIL LED DRIVER**

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2 × 42W | 48V DC | U OUT 10-40V

**DIN RAIL POWER SUPPLY**

L-W-H (mm)	ORDER CODE
72-90-63	0 0 5 - 6 5 2 0 2 1 0

220-240 V AC | 160 W | 48V DC constant voltage

**Optical accessories (optional)****HONEYCOMB LOUVER**

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 45   JUST 45   MOVE IN 45   TARO 45   TULA micro	jet black	42-3	0 0 7 - 1 9 6 5 1 8 8

**OVAL LENS**

TYPE	Ø-H (mm)	ORDER CODE
for BO 45   MOVE IN 45   TULA micro	42-3	0 0 7 - 1 9 6 5 8 8 0

SOFT LENS

TYPE	Ø-H (mm)	ORDER CODE
for ARY   BO 45   MOVE IN 45   TULA micro	42:3	0 0 7 - 1 9 6 5 9 8 0

WALLWASHER LENS

TYPE	Ø-H (mm)	ORDER CODE
for ARY   BO 45   MOVE IN 45   TULA micro	42:3	0 0 7 - 1 9 6 5 7 8 0

# Private Residence, Denmark

Danemark

## Architecte

LINK Architecture

## Lighting Design

anker & co

## Photographe

Kris Dekeijser



### Produits utilisés



**TULA suspended**



**MOVE IT 25 trimless  
system**



**SPOT LINE MOVE IT  
25**









# Trippenhuis

Pays-Bas

**Architecte**  
Arpalight


**Photographe**  
Rene de Wit Max Hart  
Nibbrig



## Produits utilisés




**SASSO 60 round**  
semi-recessed



**BO 32 / 45 / 55**  
intrack



**TULA suspended**



**MOVE IT 25 trimless**  
system



**BO 32 / 45 / 55**  
intrack 1 | 2 | 3 lamps



**SASSO 60 round**  
ceiling







