



TULA

suspended


EN Decorative suspended luminaire in aluminium; surface polished chrome or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; good glare reduction due to recessed light point plane; incl. high quality lens system; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy, either recessed or surface mounted version; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

FR Luminaire décoratif à suspension en aluminium ; surface chrome poli ou surface thermolaquée ; suspension par câble, câble d'alimentation inclus (noir ou blanche) ; recoupable à volonté ; bon anti-éblouissement grâce aux points lumineux en retrait ; incl. optique lentille de grande qualité ; avec technologie COB (Chip on Board) ou High-Power-LED pour efficacité maximale ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; cache-piton pour câblage continu ; convertisseur inclus dans le cache-piton, au choix en variante encastrée ou en saillie ; anneaux de montage au plafond pour un positionnement multiple des luminaires dans la pièce disponibles comme accessoires

Quickinfo

2700 K, 3000 K
CRI ≥ 90, 3 SDCM
up to 95 lm/W
L80 @ 50 000 h
non DIM, DALI-2, Casambi


Types



Colours



Light distributions



free positioning by
ring and hook track version
available (p. 742)

Order options

HOUSING HEIGHT

300 mm	5
500 mm	7

SUSPENSION

cable 1500 mm	
---------------	--

COLOUR TEMPERATURE

2700 K	4
3000 K	5

MATERIAL COLOUR

● chrome	4
○ traffic white RAL 9016	7
● jet black RAL 9005	8
special colours* p. 992	X

*cable always in white

BEAM ANGLE

medium 25°	M
flood 44°	F






ACCESSORY COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

Options on request

COLOUR TEMPERATURE

4000 K	
--------	--



TULA nano suspended



INSET POWER	LUMINOUS FLUX	ORDER CODE
9 W 18 Vf 500 mA	732 lm	0 4 9 - 5 L 1 0 :: 1 ▲

TULA micro suspended



INSET POWER	LUMINOUS FLUX	ORDER CODE
8,4 W 18 Vf 500 mA	798 lm	0 4 9 - 5 L 1 5 :: 1 ▲

Mounting accessories

CANOPY CEILING 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
500 mA non DIM	η 79 %	115-29	0 0 5 - 2 6 0 2 1 1 ■
500 mA DALI-2	η 81 %	115-29	0 0 5 - 2 6 0 2 1 3 ■

MOUNTING SET RECESSED WITH TRIM

for installation in ceilings from 2-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set with trim	77-49	0 0 5 - 3 5 2 1 0 1 ■

MOUNTING SET RECESSED TRIMLESS

for installation in plasterboard ceilings 9-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set trimless	75-48	0 0 5 - 3 5 1 1 0 1 7

SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting set trimless

RING

TYPE	Ø-H (mm)	ORDER CODE
ceiling mounted	50-88	0 5 0 - 0 5 1 0 2 1 ■

HOOK

TYPE	L-W-H (mm)	ORDER CODE
ceiling mounted	18-13-58	0 5 0 - 5 9 0 1 1 1 ■

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
500 mA non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 3 2
500 mA DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 3 3

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	0 0 5 - 6 5 2 0 2 1 0
160 W 48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1-2 addr.	36-88-59	0 0 5 - 6 1 2 1 0 3 0
200-1050 mA settable const. current		
2 × 42 W 48 V DC U _{OUT} 10-40 V		

for more details and components see page 981

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, lens flood 2700 K -5 %