



MOVE IT 25 S system

trimless/surface/suspended


EN Thin extruded aluminium profile with 31mm height and 28mm width groove; optionally for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5mm ceiling thickness; or for wall-/ceiling surface mounting or suspended mounting (cable suspension, height adjustment without tools, incl. black feed); optional with indirect light component for additional accentuation of the ceiling; for lighting systems; linear, 90° angle connectors or 90° CURVE segment; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised or powder coated; insets can be installed flexibly and without tools by means of magnetic holders + locking

FR Profil extrudé en aluminium plat avec 31mm de hauteur et 28mm de largeur de joint ; au choix pour un encastrément sans bord dans des plafonds en placoplâtre (montage mural ou au plafond) d'une épaisseur de 12,5mm ; ou pour un montage en surface au mur ou au plafond ou pour un montage suspendu (suspension par câble, réglage de la hauteur sans outil, câble d'alimentation noir inclus) ; en option avec composants lumineux indirects pour une accentuation supplémentaire du plafond ; pour les systèmes d'éclairage ; linéaire, connecteur d'angle 90° ou segment CURVE 90° ; avec profil de rail intégré pour fixation d'alimentation électrique et signal DALI ; surface anodisé ou thermolaquée ; montage flexible et sans outil de éléments grâce au support magnétique + verrouillage

Quickinfo

3000K
CRI ≥ 90, 2 SDCM
up to 118lm/W
L80 @ 50 000h
non DIM, DALI-2

Types



connector



corner



curve


Colours



standard



xal.com/colours



custom cut on
building site

Order options

| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| |
|----------------------|
| ● jet black RAL 9005 |
|----------------------|


Options on request

CONNECTOR

| |
|-------------|
| T-connector |
| X-connector |

INSTALLATION TRACK

| |
|------------------------|
| acoustic soft ceilings |
|------------------------|



MOVE IT 25 S trimless



INSTALLATION TRACK

| L (mm) | | ORDER CODE |
|-----------|-------------------------------------|------------------|
| 617 | channel | 050-72120÷8 |
| 1217 | channel | 050-72140÷8 |
| 2417 | channel | 050-72180÷8 |
| 3622 | channel | 050-72190÷8 |
| cust. cut | channel (non DIM) | E83131 · · · · 8 |
| cust. cut | channel (DALI-2) | E83141 · · · · 8 |
| 672x645 | channel corner* 90° | 050-72110÷8 |
| 661x661 | channel corner* ceiling to wall 90° | 050-72111÷8 |

*incl. electrical connector set

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|-------------|
| end caps (pair) | 050-7210008 |

BLIND COVER

| L (mm) | ORDER CODE |
|------------|-------------------|
| 1217 | 050-7004008 |
| 2417 | 050-7008008 |
| 3622 | 050-7009008 |
| custom cut | E83000 · · · · 8B |

blind cover can be shortened as desired

CONNECTOR SET

| TYPE | ORDER CODE |
|------------------------------------|-------------|
| linear connector (non DIM, DALI-2) | 050-2031130 |
| linear connector flexible | 050-20321÷0 |
| mechanical linear connector (pair) | 050-2011110 |



POWER FEEDER UNIT

| TYPE | ORDER CODE |
|-------------------------------------|-------------|
| non DIM 2×2,5mm ² | 050-2020110 |
| DALI-2 2×2,5 + 2×0,5mm ² | 050-2020130 |

cable length 500 mm

Electrical accessories

see following pages



Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | G |
| ● gold dust 260-M / jet black 9005 G | X |
| ● special colours* | X |

*inside always in black

MATERIAL COLOUR

ACCESSORIES

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

MATERIAL COLOUR






CABLE SUSPENSION

| | |
|--------|---|
| chrome | 0 |
| black | 8 |

Options on request

CONNECTOR

| | |
|-------------|--|
| T-connector | |
| X-connector | |



MOVE IT 25 S surface / suspended



INSTALLATION TRACK / BLIND COVER

L (mm)

| | | ORDER CODE |
|---------------------------------|-------------------------------------|-------------|
| 620 | channel | 050-73120 |
| 1220 | channel | 050-73140 |
| 2420 | channel | 050-73180 |
| 3625 | channel | 050-73190 |
| cust. cut | channel (non DIM) | E83151 |
| cust. cut | channel (DALI-2) | E83161 |
| 637x610 | channel corner* 90° | 050-73110 |
| 666x666 | channel corner* ceiling to wall 90° | 050-73111 |
| *incl. electrical connector set | | |
| 1217 | blind cover | 050-7004008 |
| 2417 | blind cover | 050-7008008 |
| 3622 | blind cover | 050-7009008 |
| cust. cut | blind cover | E83000 |

CURVE CONNECTOR

TYPE

| | ORDER CODE |
|----------------------------------|------------|
| mechanical & electrical R 300 mm | 050-731303 |
| mechanical R 300 mm | 050-731311 |

Accessories

END CAPS

TYPE

| | ORDER CODE |
|-----------------|------------|
| end caps (pair) | 050-731000 |

CONNECTOR SET

TYPE

| | ORDER CODE |
|---|-------------|
| mechanical linear conn. incl. 1500 mm cable susp. | 050-201131 |
| mechanical linear connector surface | 050-2011410 |
| mechanical & electrical linear connector | 050-2031230 |
| mechanical & electrical corner connector flex | 050-2032238 |

POWER FEEDER UNIT

TYPE

| | L (mm) | ORDER CODE |
|--------------------------------------|--------|-------------|
| non DIM 2×2,5 mm ² | 2000 | 050-2022110 |
| DALI-2 2×2,5 + 2×0,5 mm ² | 2000 | 050-2022130 |
| non DIM 2×2,5 mm ² | 4000 | 050-2024110 |
| DALI-2 2×2,5 + 2×0,5 mm ² | 4000 | 050-2024130 |

CEILING FASTENER / CABLE SUSPENSION / CANOPY

TYPE

| | L (mm) | ORDER CODE |
|------------------|--------|------------|
| ceiling fastener | 10 | 050-204111 |
| cable suspension | 1500 | 005-215211 |
| canopy | | 005-231171 |

*use every 1200 mm

Electrical accessories

see following pages

Order options

COLOUR TEMPERATURE

3000 K

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● gold dust 260-M / jet black 9005 G | |
| ● special colours* | X |

*inside always in black

MATERIAL COLOUR

ACCESSORIES

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

MATERIAL COLOUR
CABLE SUSPENSION

| | |
|--------|---|
| chrome | 0 |
| black | 8 |

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM





COLOUR TEMPERATURE

| | |
|----------------------------|--|
| 2700 K | |
| 4000 K | |
| tunable white 2700–6500 K* | |

*DALI-2 DT8

CONNECTOR

| | |
|-------------|--|
| T-connector | |
| X-connector | |



MOVE IT 25 S suspended indirect



INSTALLATION TRACK INDIRECT

| L (mm) | SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
|-----------------|--------------|---------------|-------------------|
| 620 | 6.2 W | 648 lm | 0 5 0 - 7 4 1 2 5 |
| 1220 | 15.3 W | 1810 lm | 0 5 0 - 7 4 1 4 5 |
| 2420 | 33 W | 3890 lm | 0 5 0 - 7 4 1 8 5 |
| 3625 | 51 W | 6000 lm | 0 5 0 - 7 4 1 9 5 |
| 637x610 corner* | 13.1 W | 1550 lm | 0 5 0 - 7 4 1 1 0 |

no custom cut on building side; *incl. electrical connector set

| | | |
|-----------|-------------|-------------------------|
| 1217 | blind cover | 0 5 0 - 7 0 0 4 0 0 8 |
| 2417 | blind cover | 0 5 0 - 7 0 0 8 0 0 8 |
| 3622 | blind cover | 0 5 0 - 7 0 0 9 0 0 8 |
| cust. cut | blind cover | E 8 3 0 0 0 8 B |

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|---------------------|
| end caps (pair) | 0 5 0 - 7 3 1 0 0 0 |

CONNECTOR SET

| TYPE | ORDER CODE |
|---|-----------------------|
| mechanical linear conn. incl. 1500 mm cable susp. | 0 5 0 - 2 0 1 1 3 1 |
| mechanical & electrical linear connector | 0 5 0 - 2 0 3 1 2 3 0 |
| mechanical & electrical corner connector flex | 0 5 0 - 2 0 3 2 2 3 8 |

POWER FEEDER UNIT

| TYPE | L (mm) | ORDER CODE |
|--|--------|-----------------------|
| non DIM 2 × 2,5 mm ² | 2000 | 0 5 0 - 2 0 2 2 1 1 0 |
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² | 2000 | 0 5 0 - 2 0 2 2 1 3 0 |
| non DIM 2 × 2,5 mm ² | 4000 | 0 5 0 - 2 0 2 4 1 1 0 |
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² | 4000 | 0 5 0 - 2 0 2 4 1 3 0 |

CABLE SUSPENSION / CANOPY

| TYPE | L (mm) | ORDER CODE |
|------------------|--------|---------------------|
| cable suspension | 1500 | 0 0 5 - 2 1 5 2 1 1 |
| canopy | | 0 0 5 - 2 3 1 1 7 1 |

*use every 1200 mm

Electrical accessories

see following pages



MOVE IT 25 system

trimless / surface / suspended


EN Extruded aluminium profile with 28 mm width groove; for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5 mm ceiling thickness; or for wall-/ ceiling surface mounting or suspended mounting (cable suspension, height adjustment without tools, incl. black feed); optional indirect light component for additional accentuation of the ceiling; for lighting systems; linear, 90° angle connectors or 90° CURVE segment; node connectors, up to 6 profile connection options; with power track profile for take off of supply voltage and DALI signal; surf. anod. or powder coated; insets can be installed flexibly and without tools by means of magnetic holders + locking; sound absorbing accessories available

FR Profil extrudé en aluminium avec 28 mm de largeur de joint ; pour montage sans bord dans des plafonds en placoplâtre (muraux ou au plafond) de 12,5 mm ; ou pour un montage en surface au mur ou au plafond ou pour un montage suspendu (suspension par câble, réglage de la hauteur sans outil, câble d'alimentation noir inclus) ; en option composants lumineux indirects pour une accentuation supplémentaire du plafond ; pour les systèmes d'éclairage ; linéaire, connecteur d'angle 90° ou segment CURVE 90° ; jonctions avec jusqu'à 6 options de raccordement ; avec profil de rail pour la captation de la tension d'alimentation et signal DALI; surf. anod. ou thermolaquée ; montage flexible et sans outil de éléments grâce au support magnétique + verrouillage ; accessoires doté de propriétés d'absorption acoustique


Quickinfo

3000K
CRI ≥ 90, 2 SDCM
up to 118 lm/W
L80 @ 50 000 h
non DIM, DALI-2


Types




connectors



Colours



custom cut on
building site



acoustic
elements

Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

● jet black RAL 9005






Options on request

CONNECTOR

| | |
|-------------|--|
| T-connector | |
| X-connector | |

INSTALLATION TRACK

acoustic soft ceilings



MOVE IT 25 trimless



INSTALLATION TRACK

L (mm)

| | | ORDER CODE |
|-----------|-------------------------------------|-------------|
| 617 | channel | 050-72020-8 |
| 1217 | channel | 050-72040-8 |
| 2417 | channel | 050-72080-8 |
| 3622 | channel | 050-72090-8 |
| cust. cut | channel (non DIM) | E83031-8 |
| cust. cut | channel (DALI-2) | E83041-8 |
| 672x645 | channel corner* 90° | 050-72010-8 |
| 661x661 | channel corner* ceiling to wall 90° | 050-72011-8 |

*incl. electrical connector set

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|-------------|
| end caps (pair) | 050-7200008 |

BLIND COVER

L (mm)

| | ORDER CODE |
|------------|-------------|
| 1217 | 050-7004008 |
| 2417 | 050-7008008 |
| 3622 | 050-7009008 |
| custom cut | E83000-8B |

blind cover can be shortened as desired

CONNECTOR SET

| TYPE | ORDER CODE |
|------------------------------------|-------------|
| linear connector (non DIM, DALI-2) | 050-2031130 |
| linear connector flexible | 050-20321-0 |
| mechanical linear connector (pair) | 050-2011110 |

POWER FEEDER UNIT

| TYPE | ORDER CODE |
|-------------------------|-------------|
| non DIM 2×2,5mm² | 050-2020110 |
| DALI-2 2×2,5 + 2×0,5mm² | 050-2020130 |

cable length 500 mm

Electrical accessories

see following pages

Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

INSTALLATION TRACK

| | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● gold dust 260-M / jet black 9005 G | |
| ● special colours* | X |

*inside always in black

MATERIAL COLOUR

NODE CONNECTOR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

MATERIAL COLOUR

NODE LTX / END CAP

| | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● special colours | X |

MATERIAL COLOUR

ACCESSORIES

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

MATERIAL COLOUR

CABLE SUSPENSION







| | |
|--------|---|
| chrome | 0 |
| black | 8 |

NODE CONNECTOR

MOUNTING TYPE

| | |
|----------------------------|---|
| surface* | 1 |
| 1500 mm cable susp. chrome | 3 |
| 1500 mm cable susp. black | 4 |

*only for L/T/X



MOVE IT 25 surface/suspended



INSTALLATION TRACK / BLIND COVER

L (mm)

| | |
|-----------|-------------------------------------|
| 620 | channel |
| 1220 | channel |
| 2420 | channel |
| 3625 | channel |
| cust. cut | channel (non DIM) |
| cust. cut | channel (DALI-2) |
| 637x610 | channel corner* 90° |
| 666x666 | channel corner* ceiling to wall 90° |

*incl. electrical connector set

| | |
|-----------|-------------|
| 1217 | blind cover |
| 2417 | blind cover |
| 3622 | blind cover |
| cust. cut | blind cover |

ORDER CODE

| | |
|-----------|--|
| 050-73020 | |
| 050-73040 | |
| 050-73080 | |
| 050-73090 | |
| E83051 | |
| E83061 | |
| 050-73010 | |
| 050-73011 | |

CURVE CONNECTOR

TYPE

| |
|----------------------------------|
| mechanical & electrical R 300 mm |
| mechanical R 300 mm |

ORDER CODE

| |
|------------|
| 050-730303 |
| 050-730311 |

Accessories

END CAPS

TYPE

| |
|-----------------|
| end caps (pair) |
|-----------------|

ORDER CODE

| |
|------------|
| 050-730000 |
|------------|

FLEX NODE CONNECTOR

TYPE

| |
|--|
| FLEX NODE surface mounted |
| FLEX NODE surface mounted incl. feeder |
| FLEX NODE cable suspension 1500 mm |
| FLEX NODE cable susp. 1500 mm incl. feeder |
| NODE end cap* incl. electrical connector |

ORDER CODE

| |
|------------|
| 050-203333 |
| 050-202243 |
| 050-203318 |
| 050-202228 |
| 050-730010 |

*order for every node connection (channel to node) 1 end cap

CONNECTOR SET

TYPE

| |
|---|
| mechanical linear conn. incl. 1500 mm cable susp. |
| mechanical linear connector surface |
| mechanical & electrical linear connector |
| mechanical & electrical corner connector flex |

ORDER CODE

| |
|-------------|
| 050-201131 |
| 050-2011410 |
| 050-2031230 |
| 050-2032238 |

POWER FEEDER UNIT

TYPE

| | |
|--------------------------------------|------|
| non DIM 2×2,5 mm ² | 2000 |
| DALI-2 2×2,5 + 2×0,5 mm ² | 2000 |
| non DIM 2×2,5 mm ² | 4000 |
| DALI-2 2×2,5 + 2×0,5 mm ² | 4000 |

L (mm)

ORDER CODE

| |
|-------------|
| 050-2022110 |
| 050-2022130 |
| 050-2024110 |
| 050-2024130 |

CEILING FASTENER / CABLE SUSPENSION / CANOPY

TYPE

| | |
|--------------------------------|------|
| ceiling fastener | 10 |
| cable susp. (use very 1200 mm) | 1500 |
| canopy | |

L (mm)

ORDER CODE

| |
|------------|
| 050-204111 |
| 005-215211 |
| 005-231171 |

Electrical accessories

see following pages

Acoustic elements

see following pages

Order options

COLOUR TEMPERATURE

3000 K

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

INSTALLATION TRACK

| | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● gold dust 260-M / jet black 9005 G | |
| ● special colours* | X |

*inside always in black

MATERIAL COLOUR

NODE CONNECTOR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

MATERIAL COLOUR

NODE LTX/END CAP

| | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● special colours | X |

MATERIAL COLOUR

ACCESSORIES

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

MATERIAL COLOUR

CABLE SUSPENSION

| | |
|--------|---|
| chrome | 0 |
| black | 8 |

NODE CONNECTOR

MOUNTING TYPE

| | |
|----------------------------|---|
| surface* | 1 |
| 1500 mm cable susp. chrome | 3 |
| 1500 mm cable susp. black | 4 |

*only for L/T/X

Options on request

COLOUR RENDERING INDEX






CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

2700 K
4000 K
tunable white 2700–6500 K*

*DALI-2 DT8

LUMINOUS FLUX value calculated for
3000 K, CRI ≥ 90, colour white/black



MOVE IT 25 suspended indirect



INSTALLATION TRACK INDIRECT

| L (mm) | SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
|-----------------|--------------|---------------|------------|
| 620 | 6.2 W | 648 lm | 050-74025 |
| 1220 | 15.3 W | 1810 lm | 050-74045 |
| 2420 | 33 W | 3890 lm | 050-74085 |
| 3625 | 51 W | 6000 lm | 050-74095 |
| 637x610 corner* | 13.1 W | 1550 lm | 050-74010 |

*incl. electrical connector set

| | | |
|-----------|-------------|-----------------|
| 1217 | blind cover | 050-7004008 |
| 2417 | blind cover | 050-7008008 |
| 3622 | blind cover | 050-7009008 |
| cust. cut | blind cover | E83000 ···· 8 B |

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|------------|
| end caps (pair) | 050-730000 |

FLEX NODE CONNECTOR

| TYPE | ORDER CODE |
|---|------------|
| FLEX NODE cable suspension 1500 mm | 050-20331 |
| FLEX NODE cable susp. 1500 mm incl. feeder | 050-20222 |
| FLEX NODE end cap* incl. electrical connector | 050-730010 |

*order for every node connection (channel to node) 1 end cap

CONNECTOR SET

| TYPE | ORDER CODE |
|---|-------------|
| mechanical linear conn. incl. 1500 mm cable susp. | 050-201131 |
| mechanical & electrical linear connector | 050-2031230 |
| mechanical & electrical corner connector flex | 050-2032238 |

POWER FEEDER UNIT

| TYPE | L (mm) | ORDER CODE |
|--|--------|-------------|
| non DIM 2 × 2,5 mm ² | 2000 | 050-2022110 |
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² | 2000 | 050-2022130 |
| non DIM 2 × 2,5 mm ² | 4000 | 050-2024110 |
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² | 4000 | 050-2024130 |

CABLE SUSPENSION / CANOPY

| TYPE | L (mm) | ORDER CODE |
|-------------------|--------|------------|
| cable suspension* | 1500 | 005-215211 |
| canopy | | 005-231171 |

*use every 1200 mm

Electrical accessories

see following pages

Acoustic elements

see following pages


Order options

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |



Electrical accessories

POWER SUPPLY INTRACK supply 220-240 V AC, 48 V, 50-60 Hz


| TYPE | EFFICIENCY | MOUNTING | L-W-H (mm) | ORDER CODE |
|---------------------------|------------|----------|------------|-------------|
| 100 W □ PC II η 92 % | | intrack | 403-26-46 | 050-2071038 |
| 150 W □ PC II η 92 % | | intrack | 403-26-46 | 050-2071138 |

ENEC approved, incl. feeder cable 2000 mm; DALI-2 SELV device integrated

POWER SUPPLY SURFACE supply 220-240 V AC, 48 V, 50-60 Hz

| TYPE | EFFICIENCY | MOUNTING | L-W-H (mm) | ORDER CODE |
|---------------------------|------------|----------|------------|------------|
| 60 W □ PC II η 88 % | | surface | 305-144-54 | 050-20551 |
| 100 W □ PC II η 92 % | | surface | 455-104-40 | 050-20554 |
| 150 W □ PC II η 92 % | | surface | 455-104-40 | 050-20552 |
| 250 W □ PC II η 93 % | | surface | 455-104-40 | 050-20555 |
| 320 W ⊕ PC I η 94 % | | surface | 305-144-54 | 050-20553 |

ENEC approved, incl. feeder cable 2000 mm; DALI-2 SELV device integrated



POWER SUPPLY EXTERNAL supply 220-240 V AC, 48 V, 50-60 Hz

| TYPE | EFFICIENCY | MOUNTING | L-W-H (mm) | ORDER CODE |
|---------------------------|------------|----------|------------|------------|
| 60 W □ PC II η 88 % | | external | 163-43-32 | 002-62133 |
| 100 W □ PC II η 92 % | | external | 350-30-18 | 002-62134 |
| 150 W □ PC II η 92 % | | external | 350-30-18 | 002-62135 |
| 250 W □ PC II η 93 % | | external | 400-40-22 | 002-62139 |
| 320 W ⊕ PC I η 94 % | | external | 252-90-44 | 002-60320 |


ENEC approved, incl. feeder cable 2000 mm



POWER SUPPLY BASIC 48 V

220-240 V | 50-60 Hz | □ PC II | Lifetime @ 120 W, 45° ambient temp. cascable max. 3 devices

| TYPE | EFFICIENCY/LIFETIME | W-H-D (mm) | ORDER CODE |
|-----------------------------------|---------------------|------------|-------------|
| 160 W η 94.5 % / > 100.000 h | | 72-90-63 | 005-6520210 |



DIN RAIL POWER SUPPLY PRO 48 V

220-240 V | 50-60 Hz | ⊕ PC I | MTBF @ 55° ambient temperature cascable max. 5 devices (240 W) or 3 devices (480 W)


| TYPE | EFFICIENCY/MTBF | W-H-D (mm) | ORDER CODE |
|---------------------------------|-----------------|-------------|-------------|
| 240 W η 92 % / > 400.000 h | | 60-125-100 | 005-6220110 |
| 480 W η 93 % / > 350.000 h | | 120-125-100 | 005-6220210 |



DALI-2 SELV DEVICE

| TYPE | L-W-H (mm) | ORDER CODE |
|--------------|------------|-------------|
| control unit | 213-37-25 | 050-2061130 |

necessary to create DALI-2 SELV signal; DALI power supply integrated



DALI SENSOR


| TYPE | L-W-H (mm) | ORDER CODE |
|--|------------|-------------|
| ESSENTIAL sensor (brightness & presence) | 125-28-45 | 050-2063178 |



WIRELESS TO DALI-2 CONTROL DEVICE


| TYPE | L-W-H (mm) | ORDER CODE |
|---------|------------|-------------|
| Casambi | 111-25-45 | 050-2065230 |

DALI-2 SELV device required



WIRELESS TO DALI-2 REPEATER


| TYPE | L-W-H (mm) | ORDER CODE |
|---------|------------|-------------|
| Casambi | 111-25-45 | 050-2066230 |




MIDDLE FEED

| TYPE | ORDER CODE |
|--|-------------|
| DALI-2 2 × 2,5 + 2 × 0,5 mm ² | 050-2038130 |

cable length 2000 mm



Blique by Nobis
Stockholm, SE –
by Wingårdh





JUST

spotlight inset 25/25S

Quickinfo




2700K, 3000K, 4000K, TW, CWD
CRI ≥ 90, 2 SDCM
non DIM, DALI-2

L95 @ 50 000h
JUST 32 focus up to 47lm/W


L80 @ 50 000h
JUST 45 up to 72lm/W

L90 @ 50 000h
JUST 55 up to 79lm/W

Types

| JUST 32 focus | JUST 45 | JUST 55 |
|---|---|---|
|  |  |  |
| 72 ø 32 | 80 ø 45 | 100 ø 55 |

Colours




Light distributions

JUST 32 focus



focus

JUST 45




super spot med. flood

JUST 55



spot med. flood



TW 1800-3000K
or 2700-6500K

CWD
2000-3000K

Order options

COLOUR TEMPERATURE

| | |
|--------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| 4000 K | 6 |

colour warm dim. 2000–3000 K*
tunable white 1800–3000 K**
tunable white 2700–6500 K**

*DALI-2 **DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| special colours | X |

BEAM ANGLE JUST 45

| | |
|------------|---|
| medium 23° | M |
| flood 44° | F |

BEAM ANGLE JUST 55




| | |
|------------|---|
| spot 16° | S |
| medium 23° | M |
| flood 37° | F |

Options on request

OPTICAL ACCESSORIES

elliptical sculpture foil
snoot
colour filter (red, blue, green, etc.)

only for JUST 32 focus



JUST 32 focus 17–43°



| | | | | | |
|----------|------------|-----|---------|------------|------------|
| CRI ≥ 90 | DALI 1ADDR | 48V | pending | CB pending | no flicker |
|----------|------------|-----|---------|------------|------------|

SPOTLIGHT

| INSET POWER | LUMINOUS FLUX | ORDER CODE |
|-------------|---------------|------------|
| 8.3 W | 393 lm | 050-01111 |

JUST 45



| | | | | | |
|----------|------------|-----|---------|------------|------------|
| CRI ≥ 90 | DALI 1ADDR | 48V | pending | CB pending | no flicker |
|----------|------------|-----|---------|------------|------------|

SPOTLIGHT

| INSET POWER | LUMINOUS FLUX | ORDER CODE |
|----------------------|---------------|-------------|
| 6.1 W super spot 8° | 297 lm | 050-01311 |
| 11 W | 788 lm | 050-01311 |
| 12 W CWD 2000–3000 K | 430 lm | 050-01311E3 |
| 11 W TW 1800–3000 K | 555 lm | 050-01311L3 |
| 11 W TW 2700–6500 K | 683 lm | 050-01311D3 |

JUST 55



| | | | | | |
|----------|------------|-----|---------|------------|------------|
| CRI ≥ 90 | DALI 1ADDR | 48V | pending | CB pending | no flicker |
|----------|------------|-----|---------|------------|------------|

SPOTLIGHT

| INSET POWER | LUMINOUS FLUX | ORDER CODE |
|-------------|---------------|------------|
| 15.9 W | 1300 lm | 050-01433 |
| 25.4 W | 1750 lm | 050-01423 |

Optical accessories

HONEYCOMB LOUVER

| TYPE | Ø-H (mm) | ORDER CODE |
|---------------|----------|-------------|
| JUST 32 focus | 30.4 | 007-1965178 |
| JUST 45 | 42.3 | 007-1965188 |
| JUST 55 | 50.3 | 007-1965598 |

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, lens flood 2700 K -5%, 4000 K +5%



MOVE IT 25 SYSTEM



reddot award 2019
winner



DESIGN
AWARD
2019


PIVOT

graphic light inset 25/25S

Quickinfo

2700 K, 3000 K, TW
CRI \geq 90, 3 SDCM
up to 123 lm/W
L90 @ 50 000 h
non DIM, DALI-2

Types




Colour




Light distribution



opal



tunable white
1800–4000 K



CRI \geq 98
XPECTRUM

Order options

COLOUR TEMPERATURE

| | |
|----------------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| tunable white 1800–4000 K* | L |

*DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

● jet black RAL 9005

Options on request

COLOUR RENDERING INDEX


CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

4000 K

MATERIAL COLOUR

○ traffic white RAL 9016




LIGHT INSET 25S




PIVOT

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 1 3 1 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 1 3 1 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 1 3 1 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 1 3 1 5 :: 8 0 |
| | 3000 K | 3160 lm | | |
| 32 W | 2700 K | 3570 lm | 1810 | 0 5 0 - 1 3 1 6 :: 8 0 |
| | 3000 K | 3790 lm | | |



PIVOT SUSPENDED

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 0 3 2 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 0 3 2 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 0 3 2 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 0 3 2 5 :: 8 0 |
| | 3000 K | 3160 lm | | |




LIGHT INSET 25



PIVOT

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 0 3 1 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 0 3 1 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 0 3 1 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 0 3 1 5 :: 8 0 |
| | 3000 K | 3160 lm | | |
| 32 W | 2700 K | 3570 lm | 1810 | 0 5 0 - 0 3 1 6 :: 8 0 |
| | 3000 K | 3790 lm | | |



PIVOT SUSPENDED

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|------------------------|
| 10.6 W | 2700 K | 1190 lm | 610 | 0 5 0 - 0 3 2 2 :: 8 0 |
| | 3000 K | 1260 lm | | |
| 15.9 W | 2700 K | 1780 lm | 910 | 0 5 0 - 0 3 2 3 :: 8 0 |
| | 3000 K | 1890 lm | | |
| 21.2 W | 2700 K | 2380 lm | 1210 | 0 5 0 - 0 3 2 4 :: 8 0 |
| | 3000 K | 2530 lm | | |
| 26.4 W | 2700 K | 2970 lm | 1510 | 0 5 0 - 0 3 2 5 :: 8 0 |
| | 3000 K | 3160 lm | | |



FLEXTRACK

system extension 25/25S


EN Thin extruded aluminium profile with 31mm height and 28mm width groove; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised or powder coated; for installation in two MOVE IT 25 or 25 S profiles; profile can be installed and moved without tools by means of magnetic holders+locking; mount 360° rotatable and freely slidable on one end; light insets can be installed flexibly and without tools by means of magnetic holders+locking

FR Profil extrudé en aluminium plat avec 31mm de hauteur et 28mm de largeur de joint ; avec profil de rail intégré pour fixation d'alimentation électrique et signal DALI ; surface anodisé ou thermolaquée ; à encastrer dans deux profils MOVE IT 25 ou MOVE IT 25 S ; l'profilé peut être inséré et déplacé sans outil grâce au support magnétique + verrouillage ; fixation rotatif à 360° et coulissante à volonté sur une extrémité ; montage flexible et sans outil de éléments lumineux grâce au support magnétique + verrouillage

Quickinfo

non DIM, DALI-2

Types



Colours



standard



xal.com/colours


Order options

| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

| MATERIAL COLOUR | |
|---|---|
| ● jet black RAL 9005 | 8 |
| ● traffic white 9016 / jet black 9005 P | |
| ● gold dust 260-M / jet black 9005 G | |
| ● special colours* | X |

*inside always in black


MOVE IT 25 S



FLEXTRACK


| L (mm) | ORDER CODE |
|--------|------------|
| 620 | 050-75120 |
| 920 | 050-75130 |
| 1220 | 050-75140 |
| 1520 | 050-75150 |
| 1820 | 050-75160 |

MOVE IT 25



FLEXTRACK


| L (mm) | ORDER CODE |
|--------|------------|
| 620 | 050-75020 |
| 920 | 050-75030 |
| 1220 | 050-75040 |
| 1520 | 050-75050 |
| 1820 | 050-75060 |



Quickinfo

2700 K, 3000 K, 4000 K, TW
CRI ≥ 90, 3 SDCM
up to 84 lm/W
L90 @ 50 000 h
non DIM, DALI-2

Types



Colours



Light distributions




reddot winner 2020




DESIGN
AWARD
2020

ARY rod

decorative inset 25/25S



free positioning by
ring and hook



tunable white
2200 – 4000 K

Order options

CABLE SUSPENSION

| | |
|-------------------|---|
| 1500mm | 5 |
| 2000mm with hook* | 6 |

*one ring included

COLOUR TEMPERATURE

| | |
|----------------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| 4000 K | 6 |
| tunable white 2200–4000 K* | |

*DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR


| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| special colours | X |

ACCESSORY COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |

BEAM ANGLE

| | |
|------------|---|
| medium 25° | M |
| flood 44° | F |



ARY rod



DOWNLIGHT


| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|--------------|---------------|-------------------|
| 14 W | 2700 K | 1050 lm | 0 5 0 - 0 2 1 |
| | 3000 K | 1100 lm | |
| | 4000 K | 1180 lm | |
| 5.4 W TW | 2200–4000 K | 284 lm | 0 5 0 - 0 2 1 D 3 |

ARY rod adjustable



SPOTLIGHT


| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|--------------|---------------|-------------------|
| 14 W | 2700 K | 1050 lm | 0 5 0 - 0 3 1 |
| | 3000 K | 1100 lm | |
| | 4000 K | 1180 lm | |
| 5.4 W TW | 2200–4000 K | 284 lm | 0 5 0 - 0 3 1 D 3 |



Mounting accessories

RING track mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|--------------|----------|---------------------|
| MOVE IT 25 S | 50-70 | 0 5 0 - 1 5 1 0 1 1 |
| MOVE IT 25 | 50-91 | 0 5 0 - 0 5 1 0 1 1 |



RING ceiling mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|----------------|----------|---------------------|
| MOVE IT 25S/25 | 50-88 | 0 5 0 - 0 5 1 0 2 1 |





reddot winner 2020



DESIGN
AWARD
2020


ARY cable

decorative inset 25/25S

Quickinfo

2700 K, 3000 K, 4000 K, TW
CRI ≥ 90, 3 SDCM
up to 84 lm/W
L90 @ 50 000 h
non DIM, DALI-2


Types




Colours




Light distributions



free positioning by
ring and hook



tunable white
2200 – 4000 K




TULA

decorative inset 25/25S

Quickinfo

2700 K, 3000 K, TW
CRI ≥ 90, 3 SDCM
up to 75 lm/W
L80 @ 50 000 h
non DIM, DALI-2


Types




Colours



Light distributions



free positioning by
ring and hook



tunable white
2200 – 4000 K

Order options

HOUSING HEIGHT

| | |
|--------|---|
| 300 mm | 0 |
| 500 mm | 1 |

CABLE SUSPENSION

| | |
|--------------------|---|
| 1500 mm | 7 |
| 2000 mm with hook* | 8 |

*one ring included

COLOUR TEMPERATURE

| | |
|------------------------------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| tunable white 2200 – 4000 K* | |

*DALI-2 DT8

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|--------------------------|---|
| ○ chrome | 4 |
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

ACCESSORY COLOUR

| | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |


BEAM ANGLE

| | |
|------------|---|
| medium 25° | M |
| flood 44° | F |

Options on request

COLOUR TEMPERATURE

4000 K




TULA nano suspended



DOWNLIGHT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|--------------|---------------|-----------------|
| 11W | 2700 K | 642 lm | 0 5 0 - L 1 1 1 |
| | 3000 K | 688 lm | |



TULA micro suspended




DOWNLIGHT

| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE |
|-------------|---------------|---------------|-------------------|
| 14 W | 2700 K | 998 lm | 0 5 0 - L 1 5 |
| | 3000 K | 1048 lm | |
| 5.4 W | 2200 – 4000 K | 254 lm | 0 5 0 - L 1 5 D 3 |

Mounting accessories

RING track mounted


| TYPE | Ø-H (mm) | ORDER CODE |
|--------------|----------|---------------------|
| MOVE IT 25 S | 50-70 | 0 5 0 - 1 5 1 0 1 1 |
| MOVE IT 25 | 50-91 | 0 5 0 - 0 5 1 0 1 1 |



RING ceiling mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|-----------------|----------|---------------------|
| MOVE IT 25 S/25 | 50-88 | 0 5 0 - 0 5 1 0 2 1 |






Quickinfo

2700 K, 3000 K
CRI ≥ 90, 3 SDCM
up to 55 lm/W
L80 @ 50 000 h
non DIM, DALI-2
IP 40

Types



Colours



Light distribution



Order options

CABLE SUSPENSION

| | |
|-------------------|---|
| 1500mm | 5 |
| 2000mm with hook* | 6 |

*one ring included

COLOUR TEMPERATURE

| | |
|--------|---|
| 2700 K | 4 |
| 3000 K | 5 |

CONTROL


| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

| | |
|-----------------------|---|
| ○ pure white RAL 9010 | 7 |
| ● jet black RAL 9005 | 8 |
| ● special colours | X |

ACCESSORY COLOUR

| | |
|-----------------------|---|
| ○ pure white RAL 9010 | 7 |
| ● jet black RAL 9005 | 8 |



PAL suspended



| | | | |
|-------------|---------------|-----|------|
| CRI ≥ 90 | DALI 1ADDR | 48V | IP40 |
|-------------|---------------|-----|------|


DOWNLIGHT

| INS. POWER | COLOUR TEMP. | LUM. FLUX | Ø (mm) | ORDER CODE |
|------------|--------------|-----------|--------|-------------|
| 9.1W | 2700 K | 472lm | 80 | 050-1 1 1 1 |
| | 3000 K | 498lm | | |
| 9.1W | 2700 K | 472lm | 120 | 050-1 1 3 1 |
| | 3000 K | 498lm | | |

Mounting accessories

RING track mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|--------------|----------|------------|
| MOVE IT 25 S | 50-70 | 050-151011 |
| MOVE IT 25 | 50-91 | 050-051011 |



RING ceiling mounted

| TYPE | Ø-H (mm) | ORDER CODE |
|----------------|----------|------------|
| MOVE IT 25S/25 | 50-88 | 050-051021 |




INSET POWER in watts is the current consumption excluding any ballast

LUMINOUS FLUX value calculated for CRI ≥ 90, colour white, glass

**Quickinfo**

2700 K
CRI ≥ 95, 3 SDCM
up to 72 lm/W
L90 @ 50 000 h
non DIM, DALI-2

Types**Colours**

wästberg w201 Extra small pendant

Design by Claesson Koivisto Rune

Order options


| CABLE SUSPENSION | |
|-------------------|---|
| 3000 mm | 5 |
| 3000 mm with hook | 6 |

| COLOUR TEMPERATURE | |
|--------------------|--|
| 2700 K | |

| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

| MATERIAL COLOUR | |
|--------------------------|---|
| ○ traffic white RAL 9016 | 7 |
| ● jet black RAL 9005 | 8 |


| ACCESSORY COLOUR | |
|-----------------------|---|
| ○ pure white RAL 9010 | 7 |
| ● jet black RAL 9005 | 8 |



w201 Extra small pendant s1




| DOWNLIGHT | | | | |
|-------------|--------------|---------------|------------|--|
| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE | |
| 7.9W | 2700 K | 544lm | 050-04814 | |



w201 Extra small pendant s2



| DOWNLIGHT | | | | |
|-------------|--------------|---------------|------------|--|
| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE | |
| 7.9W | 2700 K | 572lm | 050-04824 | |




w201 Extra small pendant s3



| DOWNLIGHT | | | | |
|-------------|--------------|---------------|------------|--|
| INSET POWER | COLOUR TEMP. | LUMINOUS FLUX | ORDER CODE | |
| 7.9W | 2700 K | 572lm | 050-04834 | |

Mounting accessories



| RING track mounted | | | |
|--------------------|----------|------------|--|
| TYPE | Ø-H (mm) | ORDER CODE | |
| MOVE IT 25 S | 50-70 | 050-151011 | |
| MOVE IT 25 | 50-91 | 050-051011 | |



| RING ceiling mounted | | | |
|----------------------|----------|------------|--|
| TYPE | Ø-H (mm) | ORDER CODE | |
| MOVE IT 25S/25 | 50-88 | 050-051021 | |

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI≥90, colour white

SPOT LINE / OPAL

linear inset 25


Quickinfo

2700 K, 3000 K, TW (opal)
 CRI ≥ 90 , 3 SDCM
 SPOT LINE up to 80 lm/W
 OPAL up to 101 lm/W
 L80 @ 50 000 h
 non DIM, DALI-2


Types

MOVE IT 25



SPOT LINE




OPAL



Light distributions



tunable white
1800–4000 K



CRI ≥ 98
XPECTRUM

Order options

| COLOUR TEMPERATURE | |
|--|---|
| 2700 K | 4 |
| 3000 K | 5 |
| tunable white 1800–4000 K* | L |
| *only available for opal high performance inset DALI-2 DT8 | |


| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

| MATERIAL COLOUR |
|----------------------|
| ● jet black RAL 9005 |

Options on request

| COLOUR RENDERING INDEX |
|------------------------|
| CRI ≥ 98 XPECTRUM |


| COLOUR TEMPERATURE |
|--------------------|
| 4000 K |




LIGHT INSET 25




| SPOT LINE | | | | |
|------------|--------------|-----------|--------|------------------------|
| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
| 3 × 1.4 W | 2700 K | 309lm | 155 | 0 5 0 - 0 2 2 0 :: 8 M |
| | 3000 K | 336lm | | |
| 6 × 1.4 W | 2700 K | 618lm | 305 | 0 5 0 - 0 2 2 1 :: 8 M |
| | 3000 K | 672lm | | |
| 12 × 1.4 W | 2700 K | 1240lm | 605 | 0 5 0 - 0 2 2 2 :: 8 M |
| | 3000 K | 1340lm | | |



| OPAL HIGH PERFORMANCE | | | | |
|-----------------------|--------------|-----------|--------|------------------------|
| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
| 5.3 W | 2700 K | 451lm | 305 | 0 5 0 - 0 2 1 1 :: 8 H |
| | 3000 K | 484lm | | |
| 10.6 W | 2700 K | 902lm | 605 | 0 5 0 - 0 2 1 2 :: 8 H |
| | 3000 K | 968lm | | |
| 21.3 W | 2700 K | 1800lm | 1205 | 0 5 0 - 0 2 1 4 :: 8 H |
| | 3000 K | 1940lm | | |
| 43 W | 2700 K | 3610lm | 2405 | 0 5 0 - 0 2 1 8 :: 8 H |
| | 3000 K | 3870lm | | |




LIGHT INSET 25 S



| OPAL HIGH PERFORMANCE | | | | |
|-----------------------|--------------|-----------|--------|------------------------|
| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
| 5.3 W | 2700 K | 402lm | 305 | 0 5 0 - 1 2 1 1 :: 8 H |
| | 3000 K | 432lm | | |
| 10.6 W | 2700 K | 805lm | 605 | 0 5 0 - 1 2 1 2 :: 8 H |
| | 3000 K | 864lm | | |
| 21.3 W | 2700 K | 1610lm | 1205 | 0 5 0 - 1 2 1 4 :: 8 H |
| | 3000 K | 1730lm | | |
| 43 W | 2700 K | 3220lm | 2405 | 0 5 0 - 1 2 1 8 :: 8 H |
| | 3000 K | 3460lm | | |

canyon solution for MOVE IT 25

Light distribution



spot line

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black

WALLWASHER

linear inset 25/25S


Quickinfo

2700 K, 3000 K
CRI ≥ 90 , 3 SDCM
WALLWASHER up to 81lm/W
WW flush up to 82lm/W
L80 @ 50 000 h
non DIM, DALI-2


Types

MOVE IT 25

WALLWASHER




WALLWASHER flush



MOVE IT 25 S


WALLWASHER flush



Light distribution



wall
washer



CRI ≥ 98
XPECTRUM

Order options


| | | |
|--------------------|---|----|
| COLOUR TEMPERATURE | | •• |
| 2700 K | 4 | |
| 3000 K | 5 | |
| CONTROL | | ◆ |
| non DIM | 1 | |
| DALI-2 | 3 | |

| | |
|----------------------|--|
| MATERIAL COLOUR | |
| ● jet black RAL 9005 | |

Options on request

| | |
|------------------------|--|
| COLOUR RENDERING INDEX | |
| CRI ≥ 98 XPECTRUM | |

| | |
|--------------------|--|
| COLOUR TEMPERATURE | |
| 4000 K | |




LIGHT INSET 25



WALLWASHER

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|--------------------------|
| 13 W | 2700 K | 983lm | 450 | 0 5 0 - 0 2 3 2 •• 3 8 A |
| | 3000 K | 1050lm | | |



WALLWASHER FLUSH

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|--------------------------|
| 5.6 W | 2700 K | 415lm | 305 | 0 5 0 - 0 2 1 1 •• ◆ 8 A |
| | 3000 K | 454lm | | |
| 11.2 W | 2700 K | 829lm | 605 | 0 5 0 - 0 2 1 2 •• ◆ 8 A |
| | 3000 K | 908lm | | |
| 22.3 W | 2700 K | 1660lm | 1205 | 0 5 0 - 0 2 1 4 •• ◆ 8 A |
| | 3000 K | 1820lm | | |
| 45 W | 2700 K | 3320lm | 2405 | 0 5 0 - 0 2 1 8 •• ◆ 8 A |
| | 3000 K | 3630lm | | |

Optical accessories

ANTI-GLARE GRID

| TYPE | L-W (mm) | ORDER CODE |
|------------------|----------|-----------------------|
| WALLWASHER FLUSH | 303-25 | 0 5 0 - 0 2 3 0 9 1 8 |

cluster solution to create anti-glare grid for all lengths




LIGHT INSET 25 S




WALLWASHER FLUSH

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|--------------------------|
| 5.6 W | 2700 K | 415lm | 305 | 0 5 0 - 1 2 1 1 •• ◆ 8 A |
| | 3000 K | 454lm | | |
| 11.2 W | 2700 K | 829lm | 605 | 0 5 0 - 1 2 1 2 •• ◆ 8 A |
| | 3000 K | 908lm | | |
| 22.3 W | 2700 K | 1660lm | 1205 | 0 5 0 - 1 2 1 4 •• ◆ 8 A |
| | 3000 K | 1820lm | | |
| 45 W | 2700 K | 3320lm | 2405 | 0 5 0 - 1 2 1 8 •• ◆ 8 A |
| | 3000 K | 3630lm | | |

Light distributions



wallwasher



wallwasher flush

INSET POWER in watts is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black


Quickinfo

2700 K, 3000 K
 CRI ≥ 90 , 3 SDCM
 WALL GRAZER up to 107lm/W
 BATWING up to 104lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types

MOVE IT 25 S

WALL GRAZER / BATWING




Light distributions



WALL GRAZER/BATWING

linear inset 25S




CRI ≥ 98
 XPECTRUM

Order options

| | |
|----------------------|----|
| COLOUR TEMPERATURE | •• |
| 2700 K | 4 |
| 3000 K | 5 |
| | |
| CONTROL | ◆ |
| non DIM | 1 |
| DALI-2 | 3 |
| | |
| MATERIAL COLOUR | |
| ● jet black RAL 9005 | |

Options on request

| | |
|------------------------|--|
| COLOUR RENDERING INDEX | |
| CRI ≥ 98 XPECTRUM | |
| | |
| COLOUR TEMPERATURE | |
| 4000 K | |




LIGHT INSET 25 S



WALL GRAZER


| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|-----------------------|
| 5.3 W | 2700 K | 525 lm | 305 | 0 5 0 - 1 2 1 1 : 8 S |
| | 3000 K | 564 lm | | |
| 10.6 W | 2700 K | 1050 lm | 605 | 0 5 0 - 1 2 1 2 : 8 S |
| | 3000 K | 1130 lm | | |
| 21.3 W | 2700 K | 2100 lm | 1205 | 0 5 0 - 1 2 1 4 : 8 S |
| | 3000 K | 2260 lm | | |
| 43 W | 2700 K | 4200 lm | 2405 | 0 5 0 - 1 2 1 8 : 8 S |
| | 3000 K | 4510 lm | | |




BATWING

| INS. POWER | COLOUR TEMP. | LUM. FLUX | L (mm) | ORDER CODE |
|------------|--------------|-----------|--------|-----------------------|
| 5.3 W | 2700 K | 512 lm | 305 | 0 5 0 - 1 2 1 1 : 8 B |
| | 3000 K | 550 lm | | |
| 10.6 W | 2700 K | 1020 lm | 605 | 0 5 0 - 1 2 1 2 : 8 B |
| | 3000 K | 1100 lm | | |
| 21.3 W | 2700 K | 2050 lm | 1205 | 0 5 0 - 1 2 1 4 : 8 B |
| | 3000 K | 2200 lm | | |
| 43 W | 2700 K | 4100 lm | 2405 | 0 5 0 - 1 2 1 8 : 8 B |
| | 3000 K | 4400 lm | | |

Light distributions



wall grazer



batwing

INSET POWER in watts is the current consumption excluding any ballast

LUMINOUS FLUX value calculated for CRI ≥ 90, colour black

MOVE IT 25 system

acoustic elements

EN Acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties; different versions: choice of square, rectangular or triangular design; high quality visual and tactile surface with embossed pattern; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 25 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools

FR Élément acoustique en feutre PET recyclé, autoportant, haute qualité, doué de propriétés insonorisantes ; diverses variantes : forme au choix carrée, rectangulaire ou triangulaire ; surface de haute qualité optique et tactile avec motif gaufré ; inclusions de fibres étrangères possibles ; absorption du bruit direct et du bruit réfléchi par le plafond ; pour de meilleures performances acoustiques ; à insérer dans le système suspendu MOVE IT 25 composé de jonctions et profils disponibles ; possibilité d'insertion ultérieure dans un MOVE IT suspended system déjà en place ; montage sans outil


Quickinfo

PET felt

♻️ from recycled material

🔥 available as B-s1, d0


Types



Colours



easy
mounting



sound absorption
by recycled PET


Order options

| MATERIAL COLOUR | | |
|-----------------------------------|--|---|
| <input type="radio"/> white | | W |
| <input type="radio"/> marble grey | | D |
| <input type="radio"/> black | | L |

Options on request

| MATERIAL COLOUR |
|---------------------------|
| painting in custom colour |

| DIMENSIONS |
|--------------------------|
| cut in custom dimensions |



MOVE IT 25 acoustic suspended



ACOUSTIC ELEMENT

| TYPE | L-W-H (mm) | ORDER CODE |
|-------------------|--------------|--|
| square grid inlay | 1235·1235·25 | 050-231121 <input checked="" type="checkbox"/> |
| half grid inlay | 635·1235·25 | 050-231221 <input checked="" type="checkbox"/> |
| double grid inlay | 2435·1235·25 | 050-231321 <input checked="" type="checkbox"/> |
| triangle inlay | 1195·1035·25 | 050-231421 <input checked="" type="checkbox"/> |

mounting only in MOVE IT 25 system with NODE connector + track 1220 mm, 620 mm or 2420 mm

ACOUSTIC EXAMPLES

