



CORNER


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile for mounting available in advance; suitable for wall or ceiling mounting; with double-sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en profil extrudé en alu, version arête ; aucune vis visible ; surface thermolaquée ; Profilé de luminaire pour montage livrable avant ; convient au montage mur ou plafond ; avec diffusion de lumière par 2 côtés ; cache HPO (High Performance Opal) pour éclairage homogène ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K
CRI $\geq$ 80 / 3 SDCM
jusqu'à 4,290 lm/m
jusqu'à 132 lm/W
L90 / 50000 h
non DIM
High Performance Opal
IP20

Types



Couleur



Répartition de la lumière



wall / ceiling
illumination



tunable white
2700 – 6500 K
(optional)




CORNER surface



OPAL | MID LUMEN non DIM, CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.8 W	588 mm	3000 K	1810 lm	131 lm/W	0 4 0 - 8 9 5 2 5 1 ☒ O
20.7 W	888 mm	3000 K	2720 lm	131 lm/W	0 4 0 - 8 9 5 3 5 1 ☒ O
27.6 W	1188 mm	3000 K	3620 lm	131 lm/W	0 4 0 - 8 9 5 4 5 1 ☒ O
55.0 W	2358 mm	3000 K	7250 lm	132 lm/W	0 4 0 - 8 9 5 8 5 1 ☒ O
71.0 W	3014 mm	3000 K	9340 lm	132 lm/W	0 4 0 - 8 9 5 9 5 1 ☒ O



OPAL | HIGH LUMEN non DIM, CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
20.2 W	588 mm	3000 K	2460 lm	122 lm/W	0 4 0 - 8 9 6 2 5 1 ☒ O
30.0 W	888 mm	3000 K	3680 lm	123 lm/W	0 4 0 - 8 9 6 3 5 1 ☒ O
40.0 W	1188 mm	3000 K	4910 lm	123 lm/W	0 4 0 - 8 9 6 4 5 1 ☒ O
81.0 W	2358 mm	3000 K	9820 lm	121 lm/W	0 4 0 - 8 9 6 8 5 1 ☒ O
98.0 W	3014 mm	3000 K	12700 lm	130 lm/W	0 4 0 - 8 9 6 9 5 1 ☒ O

Order options

COLOUR

pure white RAL 9010	☒ 7
jet black RAL 9005	☒ 8
white aluminium RAL 9006	☒ G