

# LINEA inner corner opal / asymmetric

wall system

058-6111617AA



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Suspendu \_\_\_\_\_

blanc , RAL9010 <sup>1</sup> \_\_\_\_\_

3520 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

Indirect 2310 lm \_\_\_\_\_

direct 1940 lm \_\_\_\_\_

total 4250 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 98 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 88 \_\_\_\_\_

MR 0.76 \_\_\_\_\_

MDER 0.69 \_\_\_\_\_

## Optique

High Performance Opal / Asymmetric \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

35 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

121 lm/W \_\_\_\_\_

29 W/m \_\_\_\_\_

## Physique

longueur 633 mm \_\_\_\_\_


largeur 633 mm \_\_\_\_\_

hauteur 100 mm \_\_\_\_\_


<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

