




## Quickinfo

2700 K, 3000 K  
CRI  $\geq$  90 / 2 SDCM, 3 SDCM  
jusqu'à 106 lm/W  
L80 / 50000 h, L85 / 50000 h  
DALI-2, non DIM  
front IP20

## Types



## Couleur



## Set de montage



## Répartition de la lumière



# MOVE IN round


recessed

**EN** Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

**FR** Élément de spot rond en aluminium, disponible dans 2 tailles ; thermolaquée ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; outil de montage spécial pour faciliter la mise en place du boîtier sans rebord proposé comme accessoire ; élément de spot réglable en hauteur sans outil : affleurant avec le plafond, dépassant de 25 mm ou 35 mm ; Technologie COB (Chip on Board) pour efficacité maximale ; pas de formation d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de grande qualité, métallisée à l'aluminium avec optique facette ; caractéristique de rayonnement précise ; bon anti-éblouissement grâce aux points lumineux en retrait ; éléments optiques comme accessoires



trimless  
installation in  
plasterboard



tool-free height  
adjustment



### MOVE IN 32 round



#### SPOT CRI ≥ 90

| FIXTURE       | COLOUR TEMP. | LUM. FLUX | FIXTURE | ORDER CODE                                                |
|---------------|--------------|-----------|---------|-----------------------------------------------------------|
| 8.7 W, 250 mA | 2700 K       | 788 lm    | 91 lm/W | 0 6 3 - 8 1 1 1 4 1 <input checked="" type="checkbox"/> S |
|               | 3000 K       | 817 lm    | 94 lm/W | 0 6 3 - 8 1 1 1 5 1 <input checked="" type="checkbox"/> S |

incl. connection cable 600mm

#### MEDIUM CRI ≥ 90

| FIXTURE       | COLOUR TEMP. | LUM. FLUX | FIXTURE | ORDER CODE                                                |
|---------------|--------------|-----------|---------|-----------------------------------------------------------|
| 8.7 W, 250 mA | 2700 K       | 821 lm    | 94 lm/W | 0 6 3 - 8 1 1 1 4 1 <input checked="" type="checkbox"/> M |
|               | 3000 K       | 852 lm    | 98 lm/W | 0 6 3 - 8 1 1 1 5 1 <input checked="" type="checkbox"/> M |

incl. connection cable 600mm

#### FLOOD CRI ≥ 90

| FIXTURE       | COLOUR TEMP. | LUM. FLUX | FIXTURE | ORDER CODE                                                |
|---------------|--------------|-----------|---------|-----------------------------------------------------------|
| 8.7 W, 250 mA | 2700 K       | 783 lm    | 90 lm/W | 0 6 3 - 8 1 1 1 4 1 <input checked="" type="checkbox"/> F |
|               | 3000 K       | 813 lm    | 93 lm/W | 0 6 3 - 8 1 1 1 5 1 <input checked="" type="checkbox"/> F |

incl. connection cable 600mm



### MOVE IN 45 round



#### SUPER SPOT CRI ≥ 90

| FIXTURE       | COLOUR TEMP. | LUM. FLUX | FIXTURE | ORDER CODE                                                |
|---------------|--------------|-----------|---------|-----------------------------------------------------------|
| 6.9 W, 600 mA | 2700 K       | 406 lm    | 59 lm/W | 0 6 3 - 8 1 2 1 4 1 <input checked="" type="checkbox"/> V |
|               | 3000 K       | 346 lm    | 50 lm/W | 0 6 3 - 8 1 2 1 5 1 <input checked="" type="checkbox"/> V |

incl. connection cable 600mm

#### SPOT CRI ≥ 90

| FIXTURE        | COLOUR TEMP. | LUM. FLUX | FIXTURE | ORDER CODE                                                |
|----------------|--------------|-----------|---------|-----------------------------------------------------------|
| 12.6 W, 350 mA | 2700 K       | 1110 lm   | 88 lm/W | 0 6 3 - 8 1 2 1 4 1 6 S                                   |
| 12.7 W, 350 mA | 2700 K       | 1120 lm   | 89 lm/W | 0 6 3 - 8 1 2 1 4 1 <input checked="" type="checkbox"/> S |
|                | 3000 K       | 1160 lm   | 92 lm/W | 0 6 3 - 8 1 2 1 5 1 <input checked="" type="checkbox"/> S |

incl. connection cable 600mm

#### MEDIUM CRI ≥ 90

| FIXTURE        | COLOUR TEMP. | LUM. FLUX | FIXTURE  | ORDER CODE                                                |
|----------------|--------------|-----------|----------|-----------------------------------------------------------|
| 13.2 W, 400 mA | 3000 K       | 1340 lm   | 102 lm/W | 0 6 3 - 8 1 2 1 5 1 6 M                                   |
| 13.4 W, 400 mA | 2700 K       | 1330 lm   | 100 lm/W | 0 6 3 - 8 1 2 1 4 1 <input checked="" type="checkbox"/> M |
|                | 3000 K       | 1380 lm   | 104 lm/W | 0 6 3 - 8 1 2 1 5 1 <input checked="" type="checkbox"/> M |

incl. connection cable 600mm

#### FLOOD CRI ≥ 90


| FIXTURE        | COLOUR TEMP. | LUM. FLUX | FIXTURE  | ORDER CODE                                                |
|----------------|--------------|-----------|----------|-----------------------------------------------------------|
| 13.2 W, 400 mA | 3000 K       | 1380 lm   | 104 lm/W | 0 6 3 - 8 1 2 1 5 1 6 F                                   |
| 13.4 W, 400 mA | 2700 K       | 1360 lm   | 102 lm/W | 0 6 3 - 8 1 2 1 4 1 <input checked="" type="checkbox"/> F |
|                | 3000 K       | 1420 lm   | 106 lm/W | 0 6 3 - 8 1 2 1 5 1 <input checked="" type="checkbox"/> F |

incl. connection cable 600mm

#### Order options


| COLOUR                 | <input checked="" type="checkbox"/> | COLOUR                 | <input checked="" type="checkbox"/> |
|------------------------|-------------------------------------|------------------------|-------------------------------------|
| chrome                 | 4                                   | chrome                 | 4                                   |
| brushed aluminium      | 6                                   | traffic white RAL 9016 | 7                                   |
| traffic white RAL 9016 | 7                                   | jet black RAL 9005     | 8                                   |
| jet black RAL 9005     | 8                                   |                        |                                     |

## Mounting accessories (required)




### MOUNTING HOUSING trimless

| TYPE                                      | COLOUR        | CEILING THICKNESS | Ø-H (mm) | ORDER CODE          |
|-------------------------------------------|---------------|-------------------|----------|---------------------|
| for installation in plasterboard ceilings | traffic white | 9-25 mm           | 63-93    | 0 6 3 - 8 8 1 1 1 7 |
| for MOVE IN 32 round                      |               |                   |          |                     |




### MOUNTING HOUSING trimless

| TYPE                                      | COLOUR        | CEILING THICKNESS | Ø-H (mm) | ORDER CODE          |
|-------------------------------------------|---------------|-------------------|----------|---------------------|
| for installation in plasterboard ceilings | traffic white | 9-25 mm           | 75-106   | 0 6 3 - 8 8 1 2 1 7 |
| for MOVE IN 45 round                      |               |                   |          |                     |



### MOUNTING HOUSING with trim for installation in ceilings, 2-25 mm

| COLOUR               | Ø-H (mm) | ORDER CODE          |
|----------------------|----------|---------------------|
| traffic white        | 65-93    | 0 6 3 - 8 8 2 1 1 7 |
| jet black            | 65-93    | 0 6 3 - 8 8 2 1 1 8 |
| for MOVE IN 32 round |          |                     |



### MOUNTING HOUSING with trim for installation in ceilings, 2-25 mm

| COLOUR               | Ø-H (mm) | ORDER CODE          |
|----------------------|----------|---------------------|
| traffic white        | 77-107   | 0 6 3 - 8 8 2 2 1 7 |
| jet black            | 77-107   | 0 6 3 - 8 8 2 2 1 8 |
| for MOVE IN 45 round |          |                     |

## Mounting accessories (optional)



### SPECIAL MOUNTING TOOL

| TYPE                                           | Ø-H (mm) | ORDER CODE          |
|------------------------------------------------|----------|---------------------|
| for MOVE IN 32 round   SPIO 20                 | 83-107   | 0 6 3 - 8 9 1 1 1 0 |
| necessary to install mounting housing trimless |          |                     |



### SPECIAL MOUNTING TOOL

| TYPE                                           | Ø-H (mm) | ORDER CODE          |
|------------------------------------------------|----------|---------------------|
| for ARY   MOVE IN 45   NOBA   TULA             | 100-107  | 0 6 3 - 8 9 1 2 1 0 |
| necessary to install mounting housing trimless |          |                     |

## Electrical accessories (required)

### POWER SUPPLY 198-264 V AC

| TYPE                          | EFFICIENCY | L-W-H (mm) | ORDER CODE        |
|-------------------------------|------------|------------|-------------------|
| 350 mA   40 W   DALI-2   PC2  | η 89 %     | 197-29-21  | 0 0 2 - 9 0 7 2 0 |
| 350 mA   22 W   non DIM   PC2 | η 89 %     | 180-30-21  | 0 0 2 - 9 0 7 2 2 |
| 400 mA   22 W   non DIM   PC2 | η 89 %     | 180-30-21  | 0 0 2 - 9 0 7 2 4 |
| 600 mA   30 W   non DIM   PC1 | η 89 %     | 180-30-21  | 0 0 2 - 9 0 7 2 6 |
| 400 mA   40 W   DALI-2   PC2  | η 89 %     | 197-29-21  | 0 0 2 - 9 0 7 2 8 |
| 600 mA   40 W   DALI-2   PC2  | η 89 %     | 197-29-21  | 0 0 2 - 9 0 7 2 9 |
| 250 mA   10 W   non DIM   PC2 | η 80 %     | 65-39-20   | 0 0 2 - 9 0 7 4 2 |
| 250 mA   10 W   DALI-2   PC2  | η 82 %     | 147-33-23  | 0 0 2 - 9 0 7 4 3 |


## Electrical accessories (optional)



### DIN RAIL LED DRIVER

| TYPE                     | L·W·H (mm) | ORDER CODE            |
|--------------------------|------------|-----------------------|
| DALI-2 DT6 1-2 addresses | 36·88·59   | 0 0 5 - 6 1 2 1 0 3 0 |

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V



### DIN RAIL POWER SUPPLY

| L·W·H (mm) | ORDER CODE            |
|------------|-----------------------|
| 72·90·63   | 0 0 5 - 6 5 2 0 2 1 0 |

220-240 V AC | 160W | 48V DC constant voltage

## Optical accessories (optional)

### HONEYCOMB LOUVER jet black

| TYPE                                                    | Ø·H (mm) | ORDER CODE            |
|---------------------------------------------------------|----------|-----------------------|
| for BO 32   JUST 32   MOVE IN 32   TARO 32   TILA 32    | 30·3     | 0 0 7 - 1 9 6 5 1 6 8 |
| for BO 45   JUST 45   MOVE IN 45   TARO 45   TULA micro | 42·3     | 0 0 7 - 1 9 6 5 1 8 8 |

### OVAL LENS

| TYPE                                | Ø·H (mm) | ORDER CODE            |
|-------------------------------------|----------|-----------------------|
| for BO 32   MOVE IN 32              | 30·3     | 0 0 7 - 1 9 6 5 8 6 0 |
| for BO 45   MOVE IN 45   TULA micro | 42·3     | 0 0 7 - 1 9 6 5 8 8 0 |

### SOFT LENS

| TYPE                                      | Ø·H (mm) | ORDER CODE            |
|-------------------------------------------|----------|-----------------------|
| for BO 32   MOVE IN 32                    | 30·3     | 0 0 7 - 1 9 6 5 9 6 0 |
| for ARY   BO 45   MOVE IN 45   TULA micro | 42·3     | 0 0 7 - 1 9 6 5 9 8 0 |

### WALLWASHER LENS

| TYPE                                      | Ø·H (mm) | ORDER CODE            |
|-------------------------------------------|----------|-----------------------|
| for BO 32   MOVE IN 32                    | 30·3     | 0 0 7 - 1 9 6 5 7 6 0 |
| for ARY   BO 45   MOVE IN 45   TULA micro | 42·3     | 0 0 7 - 1 9 6 5 7 8 0 |