



MOVE IN flex round

recessed


EN Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; spotlight head rotates 360° and tilts 90°; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

FR Élément de spot rond en aluminium, disponible dans 2 tailles ; thermolaquée ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; outil de montage spécial pour faciliter la mise en place du boîtier sans rebord proposé comme accessoire ; élément de spot réglable en hauteur sans outil : affleurant avec le plafond, dépassant de 25 mm ou 35 mm ; tête de spot pivotant à 360° et orientable à 90° ; Technologie COB (Chip on Board) pour efficacité maximale ; pas de formation d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de grande qualité, métallisée à l'aluminium avec optique facette ; caractéristique de rayonnement précise ; bon anti-éblouissement grâce aux points lumineux en retrait ; éléments optiques comme accessoires

Quickinfo

2700 K, 3000 K
CRI ≥ 90 / 2 SDCM, 3 SDCM
jusqu'à 106 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non DIM
front IP20

Types



Couleur




Set de montage




Répartition de la lumière



trimless
installation in
plasterboard



tool-free height
adjustment,
rotatable &
tiltable



MOVE IN 32 flex round



SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.7 W, 250 mA	2700 K	788 lm	91 lm/W	0 6 3 - 8 2 1 1 4 1 <input checked="" type="checkbox"/> S
	3000 K	817 lm	94 lm/W	0 6 3 - 8 2 1 1 5 1 <input checked="" type="checkbox"/> S

incl. connection cable 600 mm

MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.7 W, 250 mA	2700 K	821 lm	94 lm/W	0 6 3 - 8 2 1 1 4 1 <input checked="" type="checkbox"/> M
	3000 K	852 lm	98 lm/W	0 6 3 - 8 2 1 1 5 1 <input checked="" type="checkbox"/> M

incl. connection cable 600 mm

FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.7 W, 250 mA	2700 K	783 lm	90 lm/W	0 6 3 - 8 2 1 1 4 1 <input checked="" type="checkbox"/> F
	3000 K	813 lm	93 lm/W	0 6 3 - 8 2 1 1 5 1 <input checked="" type="checkbox"/> F

incl. connection cable 600 mm



MOVE IN 45 flex round



SUPER SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
6.9 W, 600 mA	2700 K	406 lm	59 lm/W	0 6 3 - 8 2 2 1 4 1 <input checked="" type="checkbox"/> V
	3000 K	346 lm	50 lm/W	0 6 3 - 8 2 2 1 5 1 <input checked="" type="checkbox"/> V

incl. connection cable 600 mm

SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
12.6 W, 350 mA	2700 K	1110 lm	88 lm/W	0 6 3 - 8 2 2 1 4 1 6 S
12.7 W, 350 mA	2700 K	1120 lm	89 lm/W	0 6 3 - 8 2 2 1 4 1 <input checked="" type="checkbox"/> S
	3000 K	1160 lm	92 lm/W	0 6 3 - 8 2 2 1 5 1 <input checked="" type="checkbox"/> S

incl. connection cable 600 mm

MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
13.2 W, 400 mA	3000 K	1340 lm	102 lm/W	0 6 3 - 8 2 2 1 5 1 6 M
13.4 W, 400 mA	2700 K	1330 lm	100 lm/W	0 6 3 - 8 2 2 1 4 1 <input checked="" type="checkbox"/> M
	3000 K	1380 lm	104 lm/W	0 6 3 - 8 2 2 1 5 1 <input checked="" type="checkbox"/> M

incl. connection cable 600 mm

FLOOD CRI ≥ 90





















FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
13.2 W, 400 mA	3000 K	1380 lm	104 lm/W	0 6 3 - 8 2 2 1 5 1 6 F
13.4 W, 400 mA	2700 K	1360 lm	102 lm/W	0 6 3 - 8 2 2 1 4 1 <input checked="" type="checkbox"/> F
	3000 K	1420 lm	106 lm/W	0 6 3 - 8 2 2 1 5 1 <input checked="" type="checkbox"/> F

incl. connection cable 600 mm





Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
chrome	4	chrome	4
brushed aluminium	6	traffic white RAL 9016	7
traffic white RAL 9016	7	jet black RAL 9005	8
jet black RAL 9005	8		

Mounting accessories (required)

 54	 200 non DIM	 230 DALI-2	MOUNTING HOUSING trimless				
			 92				
		 ø 63					
			TYPE	COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
			for installation in plasterboard ceilings	traffic white	9-25 mm	63-93	0 6 3 - 8 8 1 1 1 1 7
			for MOVE IN 32 round				
 65	 200 non DIM	 230 DALI-2	MOUNTING HOUSING trimless				
			 106				
		 ø 75					
			TYPE	COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
			for installation in plasterboard ceilings	traffic white	9-25 mm	75-106	0 6 3 - 8 8 1 2 1 1 7
			for MOVE IN 45 round				
 54	 200 non DIM	 230 DALI-2	MOUNTING HOUSING with trim for installation in ceilings, 2-25 mm				
			 93				
		 ø 65					
			COLOUR		Ø-H (mm)	ORDER CODE	
			traffic white		65-93	0 6 3 - 8 8 2 1 1 1 7	
			jet black		65-93	0 6 3 - 8 8 2 1 1 1 8	
			for MOVE IN 32 round				
 65	 200 non DIM	 230 DALI-2	MOUNTING HOUSING with trim for installation in ceilings, 2-25 mm				
			 107				
		 ø 77					
			COLOUR		Ø-H (mm)	ORDER CODE	
			traffic white		77-107	0 6 3 - 8 8 2 2 1 1 7	
			jet black		77-107	0 6 3 - 8 8 2 2 1 1 8	
			for MOVE IN 45 round				


Mounting accessories (optional)

 107  ø 83	SPECIAL MOUNTING TOOL			
	TYPE		Ø-H (mm)	ORDER CODE
	for MOVE IN 32 round SPIO 20		83-107	0 6 3 - 8 9 1 1 1 1 0
	necessary to install mounting housing trimless			
 107  ø 100	SPECIAL MOUNTING TOOL			
	TYPE		Ø-H (mm)	ORDER CODE
	for ARY MOVE IN 45 NOBA trimless TULA		100-107	0 6 3 - 8 9 1 2 1 1 0
	necessary to install mounting housing trimless			


Electrical accessories (required)

POWER SUPPLY 198-264 V AC				
TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE	
350 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 0	
350 mA 22 W non DIM PC2	η 89 %	180-30-21	0 0 2 - 9 0 7 2 2	
400 mA 22 W non DIM PC2	η 89 %	180-30-21	0 0 2 - 9 0 7 2 4	
600 mA 30 W non DIM PC1	η 89 %	180-30-21	0 0 2 - 9 0 7 2 6	
400 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 8	
600 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 9	
250 mA 10 W non DIM PC2	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2	
250 mA 10 W DALI-2 PC2	η 82 %	147-33-23	0 0 2 - 9 0 7 4 3	

Electrical accessories (optional)



DIN RAIL LED DRIVER		
TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36·88·59	0 0 5 - 6 1 2 1 0 3 0
200 -1050 mA settable const. current 2×42W 48V DC U OUT 10–40V		



DIN RAIL POWER SUPPLY		
L·W·H (mm)		ORDER CODE
72·90·63		0 0 5 - 6 5 2 0 2 1 0
220-240 V AC 160W 48V DC constant voltage		

Optical accessories (optional)

HONEYCOMB LOUVER jet black

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 JUST 32 MOVE IN 32 TARO 32 TILA 32	30·3	0 0 7 - 1 9 6 5 1 6 8
for BO 45 JUST 45 MOVE IN 45 TARO 45 TULA micro	42·3	0 0 7 - 1 9 6 5 1 8 8

OVAL LENS

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 MOVE IN 32	30·3	0 0 7 - 1 9 6 5 8 6 0
for BO 45 MOVE IN 45 TULA micro	42·3	0 0 7 - 1 9 6 5 8 8 0

SOFT LENS

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 MOVE IN 32	30·3	0 0 7 - 1 9 6 5 9 6 0
for ARY BO 45 MOVE IN 45 TULA micro	42·3	0 0 7 - 1 9 6 5 9 8 0

WALLWASHER LENS

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 MOVE IN 32	30·3	0 0 7 - 1 9 6 5 7 6 0
for ARY BO 45 MOVE IN 45 TULA micro	42·3	0 0 7 - 1 9 6 5 7 8 0