




Quickinfo

2700 K, 3000 K
 CRI \geq 90 / 2 SDCM, 3 SDCM
 jusqu'à 106 lm/W
 L80 / 50000 h, L85 / 50000 h
 DALI-2, non DIM
 front IP20

Types



Couleur



Set de montage



Répartition de la lumière



MOVE IN 45 square

recessed

EN Square spotlight element in aluminium; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25mm or 35mm; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

FR Élément de spot carré en aluminium ; thermolaquée ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; outil de montage spécial pour faciliter la mise en place du boîtier sans rebord proposé comme accessoire ; élément de spot réglable en hauteur sans outil : affleurant avec le plafond, dépassant de 25mm ou 35mm ; Technologie COB (Chip on Board) pour efficacité maximale ; pas de formation d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de grande qualité, métallisé à l'aluminium avec optique facettée ; caractéristique de rayonnement précise ; bon anti-éblouissement grâce aux points lumineux en retrait ; éléments optiques comme accessoires



trimless
installation in
plasterboard



tool-free height
adjustment



MOVE IN 45 square



SUPER SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
6.9 W, 600 mA	2700 K	406 lm	59 lm/W	0 6 3 - 8 4 2 1 4 1 <input checked="" type="checkbox"/> V
	3000 K	346 lm	50 lm/W	0 6 3 - 8 4 2 1 5 1 <input checked="" type="checkbox"/> V

incl. connection cable 600mm

SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
12.6 W, 350 mA	2700 K	1110 lm	88 lm/W	0 6 3 - 8 4 2 1 4 1 6 S
12.7 W, 350 mA	2700 K	1120 lm	89 lm/W	0 6 3 - 8 4 2 1 4 1 <input checked="" type="checkbox"/> S
	3000 K	1160 lm	92 lm/W	0 6 3 - 8 4 2 1 5 1 <input checked="" type="checkbox"/> S

incl. connection cable 600mm

MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
13.2 W, 400 mA	3000 K	1340 lm	102 lm/W	0 6 3 - 8 4 2 1 5 1 6 M
13.4 W, 400 mA	2700 K	1330 lm	100 lm/W	0 6 3 - 8 4 2 1 4 1 <input checked="" type="checkbox"/> M
	3000 K	1380 lm	104 lm/W	0 6 3 - 8 4 2 1 5 1 <input checked="" type="checkbox"/> M

incl. connection cable 600mm

FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
13.2 W, 400 mA	3000 K	1380 lm	104 lm/W	0 6 3 - 8 4 2 1 5 1 6 F
13.4 W, 400 mA	2700 K	1360 lm	102 lm/W	0 6 3 - 8 4 2 1 4 1 <input checked="" type="checkbox"/> F
	3000 K	1420 lm	106 lm/W	0 6 3 - 8 4 2 1 5 1 <input checked="" type="checkbox"/> F

incl. connection cable 600mm

Mounting accessories (required)



MOUNTING HOUSING trimless

TYPE	COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
for installation in plasterboard ceilings	traffic white	9-25 mm	80-54	0 6 3 - 8 8 3 2 1 1 7

for MOVE IN 45 square



MOUNTING HOUSING with trim for installation in ceilings, 2-25 mm

COLOUR	L-W-H (mm)	ORDER CODE
traffic white	78-78-55	0 6 3 - 8 8 4 2 1 1 7
jet black	78-78-55	0 6 3 - 8 8 4 2 1 1 8

for MOVE IN 45 square

Mounting accessories (optional)



SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
for ARY MOVE IN 45 NOBA TULA	100-107	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
chrome	4	chrome	4
brushed aluminium	6	traffic white RAL 9016	7
traffic white RAL 9016	7	jet black RAL 9005	8
jet black RAL 9005	8		

Electrical accessories (required)

POWER SUPPLY 198-264 V AC

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
350 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 0
350 mA 22 W non DIM PC2	η 89 %	180-30-21	0 0 2 - 9 0 7 2 2
400 mA 22 W non DIM PC2	η 89 %	180-30-21	0 0 2 - 9 0 7 2 4
600 mA 30 W non DIM PC1	η 89 %	180-30-21	0 0 2 - 9 0 7 2 6
400 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 8
600 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 9


Electrical accessories (optional)



DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V



DIN RAIL POWER SUPPLY

L-W-H (mm)	ORDER CODE
72-90-63	0 0 5 - 6 5 2 0 2 1 0

220-240 V AC | 160W | 48V DC constant voltage

Optical accessories (optional)

HONEYCOMB LOUVER

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 45 JUST 45 MOVE IN 45 TARO 45 TULA micro	jet black	42:3	0 0 7 - 1 9 6 5 1 8 8

Hotel Stoiser

Autriche

Architecte

EDERARCH ZT GmbH

Lighting Design

Eugen Schöberl

Photographe

Miriam Raneburger



Produits utilisés



**MOVE IN 45 square
recessed**



