

SASSO 60 round downlight

trimless exposed concrete

048-2602E17F 048-2695210 002-90762



Projet / Type _____

Notes _____

Quantité / Date _____



↑ IP20
↓ IP40

220-240V

360°

X-PERT

X-PERT

Général

Plafond , Encastré

rotation 360°

blanc , RAL9016 ¹

avant IP40 , arrière IP20

752 lm

LED

colour warm dimming

1800 K - 3000 K

CRI ≥ 90

L85 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 101 , R_f: 94 , R_{f(1-5)}: 96

MR 0.64

MDER 0.58

Optique

flood

angle de faisceau 36°

UGR < 19

P_{stLM} ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

12.0 W

CP2 220-240V

63 lm/W

1 DALI Addr.

Physique

sans bord

longueur 230 mm

largeur 230 mm

hauteur 162 mm

2.41 kg


Découpe

profondeur de l'encastrement 120 mm



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

