

# MINO 60 high lumen

ceiling offset


046-47M3637H



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Surface \_\_\_\_\_

blanc , RAL9010 <sup>1</sup> \_\_\_\_\_

2610 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

Résistant aux impacts de balles et ballons DIN 18032-3 \_\_\_\_\_

2280 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

MR 0.72 \_\_\_\_\_

MDER 0.65 \_\_\_\_\_

## Optique

High Performance Opal \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

17.5 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

130 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

20 W/m \_\_\_\_\_

## Physique

longueur 875 mm \_\_\_\_\_

largeur 60 mm \_\_\_\_\_


hauteur 90 mm \_\_\_\_\_

2.44 kg \_\_\_\_\_


<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

