

# MINO 60 mid lumen


ceiling offset  
046-47L8617H



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Surface \_\_\_\_\_

blanc , RAL9010 <sup>1</sup> \_\_\_\_\_

1540 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

Résistant aux impacts de balles et ballons DIN 18032-3 \_\_\_\_\_

3620 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

MR 0.72 \_\_\_\_\_

MDER 0.65 \_\_\_\_\_

## Optique

High Performance Opal \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

26.6 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

136 lm/W \_\_\_\_\_

11 W/m \_\_\_\_\_

## Physique

longueur 2347 mm \_\_\_\_\_


largeur 60 mm \_\_\_\_\_

hauteur 90 mm \_\_\_\_\_


5.8 kg \_\_\_\_\_

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

