

# INO TRIPLE circle

suspended

034-384553GH



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond | Suspendu \_\_\_\_\_

gris | RAL 9006 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

direct 16000 lm \_\_\_\_\_

total 19100 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>f(-15)</sub>: 89 \_\_\_\_\_

MR 0.61 | MDER 0.55 \_\_\_\_\_

## Optique

High Performance Opal | opal (lambertsch) \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> | SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

DALI-2 | 3 DALI Addr. \_\_\_\_\_

CP1 | 220-240 V \_\_\_\_\_

système 150 W \_\_\_\_\_

## Physique

câble 5000 mm \_\_\_\_\_

diamètre 1455 mm | hauteur 60 mm \_\_\_\_\_

14 kg \_\_\_\_\_

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Dessin de fabrication



## Notice de montage

