

# SASSO 60 round downlight

trim

048-2602612F 048-269631G 002-90762



Projet / Type
Notes
Quantité / Date



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

## Général

Plafond , Encastré
rotation 360°
chrome
Set de montage gris argent
avant IP44 , arrière IP20
1140 lm

## LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>(1-15)</sub> : 89
MR 0.81
MDER 0.74

## Optique

flood
angle de faisceau 46°
UGR < 19 , ≥ 65° < 1500 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Electrique

DALI-2
12.6 W
CP2 220-240V
90 lm/W
1 DALI Addr.

## Physique


bord
diamètre 80 mm
hauteur 48 mm

## Découpe

diamètre 73 mm
épaisseur min. du plafond 2 mm
épaisseur max. du plafond 25 mm
profondeur de l'encastrement 110 mm

<sup>1</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

