

SASSO 60 round downlight

trim

048-2602412W 048-269631G 002-90771



Projet / Type
Notes
Quantité / Date



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

Général

Plafond , Encastré
rotation 360°
chrome
Set de montage gris argent
avant IP44 , arrière IP20
1030 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 2 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Optique

wide flood
angle de faisceau 55°
≥65° <1500 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Electrique

non DIM
12.6 W
CP2 220-240V
82 lm/W

Physique


bord
diamètre 80 mm
hauteur 48 mm

Découpe

diamètre 73 mm
épaisseur min. du plafond 2 mm
épaisseur max. du plafond 25 mm
profondeur de l'encastrement 60 mm

¹ Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

