



UNICO Q1 sensor

recessed

EN UNICO Q1 sensor; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; clank-free

FR UNICO Q1 sensor ; montage sans outil en kit de montage par système à déclic à bille ; installation électrique facile par enfichage protégé contre les inversions de polarité ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; encastrement possible dans différents boîtiers ; sans distorsions

Quickinfo

DALI-2 ESSENTIAL sensor, DALI-2 SENSE sensor
front IP20

Types

trim



□ 63

trimless



□ 47

Couleur



Set de montage




DiiA® standards
251, 252, 253



one luminaire
multiple scenes



plug / socket
connector



black & gold
reflector
(optional)



tunable white
2700 – 5000 K
(optional)



UNICO Q1 sensor essential



COLOUR	ORDER CODE
jet black	0 9 0 - 7 Q 1 0 0 0 0




UNICO Q1 sensor sense



COLOUR	ORDER CODE
jet black	0 9 0 - 7 Q 1 0 0 1 0

Mounting accessories (required)



MOUNTING SET trimless

TYPE	L·W·H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/20/25 mm	47·47·47	0 9 0 - 7 Q 1 0 1 0 0
for UNICO Q1		



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	63·63·30	0 9 0 - 7 Q 1 0 2 0 B
traffic white	63·63·30	0 9 0 - 7 Q 1 0 2 0 W
for UNICO Q1		

Order options

COLOUR
jet black
RAL 9005