



UNICO Q1 sensor

recessed

EN UNICO Q1 sensor; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; clank-free

FR UNICO Q1 sensor ; montage sans outil en kit de montage par système à déclic à bille ; installation électrique facile par enfichage protégé contre les inversions de polarité ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; encastrement possible dans différents boîtiers ; sans distorsions

Quickinfo

DALI-2 ESSENTIAL sensor, DALI-2 SENSE sensor
front IP20

Types

trim



□ 63

trimless



□ 47

Couleur



Set de montage




DiiA® standards
251, 252, 253



one luminaire
multiple scenes



plug / socket
connector



black & gold
reflector
(optional)



tunable white
2700 – 5000 K
(optional)



UNICO Q1 sensor essential



| COLOUR | ORDER CODE |
|-----------|-----------------------|
| jet black | 0 9 0 - 7 Q 1 0 0 0 0 |




UNICO Q1 sensor sense



| COLOUR | ORDER CODE |
|-----------|-----------------------|
| jet black | 0 9 0 - 7 Q 1 0 0 1 0 |

Mounting accessories (required)



MOUNTING SET trimless

| TYPE | L·W·H (mm) | ORDER CODE |
|--|------------|-----------------------|
| for plasterboard ceilings 12.5/15/20/25 mm | 47·47·47 | 0 9 0 - 7 Q 1 0 1 0 0 |
| for UNICO Q1 | | |



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

| COLOUR | L·W·H (mm) | ORDER CODE |
|---------------|------------|-----------------------|
| jet black | 63·63·30 | 0 9 0 - 7 Q 1 0 2 0 B |
| traffic white | 63·63·30 | 0 9 0 - 7 Q 1 0 2 0 W |
| for UNICO Q1 | | |

Order options

| COLOUR |
|-----------|
| jet black |
| RAL 9005 |