

# MINO 60 high lumen

surface

046-41M4038Z



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Surface

noir , RAL9005 <sup>1</sup>

1770 lm/m

IP20

2070 lm

## LED

3000 K

CRI  $\geq$  90

L90 / 50000 h

sécurité photobio. RG 0 - aucun risque

MacAdam initial  $\leq$  3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

## Optique

Microprismatic

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Electrique

DALI-2

23.3 W

CP1 220-240V

89 lm/W

1 DALI Addr.

20 W/m

## Physique

longueur 1180 mm

largeur 60 mm

hauteur 80 mm

3.3 kg

## Répartition de la lumière

## Dessin de fabrication



<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage

## Calculateur d'éclairage

