

# MINO 60 high lumen

surface

046-41M313GG



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Surface \_\_\_\_\_

gris , RAL9006 <sup>1</sup> \_\_\_\_\_

1930 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

1680 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial  $\leq$  3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 92 , R<sub>(1-15)</sub>: 90 \_\_\_\_\_

MR 0.81 \_\_\_\_\_

MDER 0.74 \_\_\_\_\_

## Optique

Microprismatic \_\_\_\_\_

PstLM  $\leq$  1.0 <sup>2</sup> \_\_\_\_\_

SVM  $\leq$  0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

17.5 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

96 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

20 W/m \_\_\_\_\_

## Physique

longueur 880 mm \_\_\_\_\_

largeur 60 mm \_\_\_\_\_

hauteur 80 mm \_\_\_\_\_

2.59 kg \_\_\_\_\_

## Répartition de la lumière

## Dessin de fabrication



<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

