

# MINO 60 high lumen

surface

046-4135D3GH



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Surface \_\_\_\_\_

gris , RAL9006 <sup>1</sup> \_\_\_\_\_

2550 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

3760 lm \_\_\_\_\_

## LED

tunable white \_\_\_\_\_

2700 K - 6500 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

MR 0.48 \_\_\_\_\_

MDER 0.44 \_\_\_\_\_

## Optique

High Performance Opal \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

DALI-2 DT8 \_\_\_\_\_

32 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

118 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

21 W/m \_\_\_\_\_

## Physique

longueur 1480 mm \_\_\_\_\_

largeur 60 mm \_\_\_\_\_

hauteur 80 mm \_\_\_\_\_


3.8 kg \_\_\_\_\_

<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

