

# NOBA 40 adjustable

MOVE IT 10

030-6800436



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond / mur , Rail \_\_\_\_\_

inclinaison max 90° \_\_\_\_\_

rotation 365° \_\_\_\_\_

aluminium brossé \_\_\_\_\_

IP20 \_\_\_\_\_

382 lm \_\_\_\_\_

insert optique 121 lm/W<sup>1</sup> \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optique

wide flood \_\_\_\_\_

angle de faisceau 69° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

48 V \_\_\_\_\_

luminaire 3.5 W \_\_\_\_\_

insert optique 3.2 W \_\_\_\_\_

CP3 \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Physique

diamètre 40 mm \_\_\_\_\_

hauteur 40 mm \_\_\_\_\_

0.22 kg \_\_\_\_\_

<sup>1</sup> y compris la prise en compte des pertes optiques.  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)


## Répartition de la lumière



wide flood 69°

h (m)	EO° (lx)	ø (m)
1	338	1.37
2	84	2.74
3	38	4.12
4	21	5.49
5	14	6.86

## Dessin de fabrication



## Notice de montage

