

# VITA vertical 1013 direct / indirect

wall

099-9166Y36A



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Mur , Surface \_\_\_\_\_

aluminium anodisé \_\_\_\_\_

IP20 \_\_\_\_\_

Indirect 5740 lm \_\_\_\_\_

direct 5740 lm \_\_\_\_\_

total 11480 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI  $\geq$  97 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial  $\leq$  3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 96 , R<sub>t(1-5)</sub>: 97 \_\_\_\_\_

MR 0.68 \_\_\_\_\_

MDER 0.61 \_\_\_\_\_

## Optique

Linear Prismatic \_\_\_\_\_

PstLM  $\leq$  1.0 <sup>1</sup> \_\_\_\_\_

SVM  $\leq$  0.4 <sup>1</sup> \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

123 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

93 lm/W \_\_\_\_\_

2 DALI Addr. \_\_\_\_\_

## Physique

longueur 1013 mm \_\_\_\_\_


largeur 160 mm \_\_\_\_\_

hauteur 70 mm \_\_\_\_\_


1.7 kg \_\_\_\_\_

<sup>1</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage

