



MOVE IN flex

recessed


EN Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25mm or 35mm; spotlight head rotates 360° and tilts 90°; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

FR Élément de spot rond en aluminium, disponible dans 2 tailles ; thermolaquée ; montage sans outil en kit de montage (sans bord ou avec bord continu) par système à déclic à bille ; outil de montage spécial pour faciliter la mise en place du boîtier sans rebord proposé comme accessoire ; élément de spot réglable en hauteur sans outil : affleurant avec le plafond, dépassant de 25mm ou 35mm ; tête de spot pivotant à 360° et orientable à 90° ; Technologie COB (Chip on Board) pour efficacité maximale ; pas de formation d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; réflecteur de grande qualité, métallisée à l'aluminium avec optique facette ; caractéristique de rayonnement précise ; bon anti-éblouissement grâce aux points lumineux en retrait ; éléments optiques comme accessoires

Quickinfo

2700 K, 3000 K
 CRI ≥ 90, 2 SDCM
 MOVE IN 32 up to 86lm/W
 MOVE IN 45 up to 95lm/W
 L80 @ 50 000 h
 non DIM, DALI-2

Types





Inset colours



Housing colours



Light distributions



tool-free height
 adjustment,
 rotatable & tiltable



trimless
 installation in
 plasterboard

Order options

COLOUR TEMPERATURE	☐☐
2700K	4
3000K	5

INSET COLOUR	☑
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4

HOUSING COLOUR	■
○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE	▲
MOVE IN 32/45	
super spot 8°*	V
spot 18°/14°	S
medium 23°/24°	M
flood 37°/39°	F

*only for MOVE IN 45

Options on request

INSET COLOUR	
● gun metal	_____
● brushed brass	_____

HOUSING COLOUR	
special colours	_____

POWER SUPPLY	
DIM 1-10V	_____



MOVE IN 32 flex



SPOTLIGHT incl. connection cable 600 mm

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.8 W 36 Vf 250 mA	755 lm	0 6 3 - 8 2 1 1 ☐ ☑ ▲

MOVE IN 45 flex



SPOTLIGHT incl. connection cable 600 mm

INSET POWER	LUMINOUS FLUX	ORDER CODE
12.8 W 37 Vf 350 mA	spot 1010 lm	0 6 3 - 8 2 2 1 ☐ ☑ S
13.5 W 36 Vf 400 mA	1280 lm	0 6 3 - 8 2 2 1 ☐ ☑ ▲
6.9 W 11 Vf 600 mA	super spot 356 lm	0 6 3 - 8 2 2 1 ☐ ☑ V

*do not use optical filters

Mounting accessories

MOUNTING HOUSING TRIMLESS

for installation in plasterboard ceilings 9-25 mm

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	63-93	0 6 3 - 8 8 1 1 1 1 7
MOVE IN 45	75-106	0 6 3 - 8 8 1 2 1 1 7

MOUNTING HOUSING WITH TRIM

for installation in ceilings from 2-25 mm

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	65-93	0 6 3 - 8 8 2 1 1 1 ☐
MOVE IN 45	77-107	0 6 3 - 8 8 2 2 1 1 ☐

SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	83-9	0 6 3 - 8 9 1 1 1 1 0
MOVE IN 45	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, ☐ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
250 mA non DIM	η 80%	65-39-20	0 0 2 - 9 0 7 4 2
250 mA DALI-2	η 82%	147-33-23	0 0 2 - 9 0 7 4 3
350 mA non DIM	η 85%	180-30-21	0 0 2 - 9 0 7 2 2
350 mA DALI-2	η 85%	197-29-21	0 0 2 - 9 0 7 2 0
400 mA non DIM	η 88%	180-30-21	0 0 2 - 9 0 7 2 4
400 mA DALI-2	η 86%	197-29-21	0 0 2 - 9 0 7 2 8
600 mA non DIM	η 87%	180-30-21	0 0 2 - 9 0 7 2 6
600 mA DALI-2	η 88%	197-29-21	0 0 2 - 9 0 7 2 9

MOVE IN 32 trimless revision opening required; *insert before mounting set with trim

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	0 0 5 - 6 5 2 0 2 1 0
160 W 48V DC constant voltage		
LED DRIVER DALI-2 DT6 1-2 addr.	36-88-59	0 0 5 - 6 1 2 1 0 3 0
200-1050 mA settable const. current		
2 x 42W 48V DC U _{OUT} 10-40V		

for more details and components see page Seite 981

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN flex 32	30-3	0 0 7 - 1 9 6 5 1 6 8
MOVE IN flex 45	42-3	0 0 7 - 1 9 6 5 1 8 8

for more accessories see BO intrack; do not use optical filters for 45 super spot

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000K, CRI ≥ 90, colour white, reflector flood 2700K -6%