

# NOBA 60 adjustable

MOVE IT 10

030-6820533



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond / mur , Rail \_\_\_\_\_

inclinaison max 90° \_\_\_\_\_

rotation 365° \_\_\_\_\_

laiton brossé \_\_\_\_\_

IP20 \_\_\_\_\_

903 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f1-15</sub>: 88 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.53 \_\_\_\_\_

## Optique

Wide Flood \_\_\_\_\_

angle de faisceau 67° \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

8.1 W \_\_\_\_\_

CP3 \_\_\_\_\_

111 lm/W \_\_\_\_\_


1 DALI Addr. \_\_\_\_\_

## Physique

diamètre 60 mm \_\_\_\_\_

hauteur 60 mm \_\_\_\_\_

## Répartition de la lumière



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	858	1.31
2	215	2.63
3	95	3.94
4	54	5.26
5	34	6.57

## Dessin de fabrication



## Notice de montage

