

# TILA 16 adjustable

MOVE IT 10  
030-6500639F



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond / mur , Rail \_\_\_\_\_

inclinaison max 135° \_\_\_\_\_

rotation 365° \_\_\_\_\_

or rose \_\_\_\_\_

IP20 \_\_\_\_\_

190 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 94 , R<sub>f</sub>: 87 , R<sub>(f-15)</sub>: 90 \_\_\_\_\_

MR 0.86 \_\_\_\_\_

MDER 0.78 \_\_\_\_\_

## Optique

Flood \_\_\_\_\_

angle de faisceau 31° \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

3.3 W \_\_\_\_\_

CP3 \_\_\_\_\_

58 lm/W \_\_\_\_\_


1 DALI Addr. \_\_\_\_\_

## Physique

diamètre 16 mm \_\_\_\_\_

hauteur 80 mm \_\_\_\_\_


## Répartition de la lumière



flood 31°

h (m)	E0° (lx)	ø (m)
1	631	0.56
2	158	1.12
3	70	1.67
4	39	2.23
5	25	2.79

## Dessin de fabrication



## Notice de montage

